



# 3000 4T 20W-50

Lubricant for 4 stroke motorcycle engine

## TYPE OF USE

Street & road bikes, trails, off road bikes, fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines fitted with catalytic converters or not.

Other uses : Scooters, ATV, mopeds...

## PERFORMANCE

STANDARD                      API SG  
APPROVALS                    JASO MA under N° M033MOT059  
Meets Harley Davidson specifications

Lubricant specially reinforced with extreme pressure additives for gearbox protection and life time of gears.

High lubricating properties which decrease wear and increase engine life time.

High detergent and dispersive properties for engine cleanliness.

Compatible with catalytic converters.

JASO MA approved to ensure perfect operating conditions for wet clutches.

## RECOMMENDATIONS

Oil change: according to manufacturers' requirements and to be adjusted according to using conditions.  
Can be mixed with synthetic or mineral lubricants.

## PROPERTIES

Viscosity grade	SAE J 300	20W-50
Density at 20°C (68°F)	ASTM D1298	0.883
Viscosity at 40°C (104°F)	ASTM D445	162.8 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	19.57 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	137
Pour point	ASTM D97	-2°C / -17°F
Flash point	ASTM D92	222°C / 432°F
TBN	ASTM D 2896	8.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Site Web : [www.motul.fr](http://www.motul.fr)

8370

10/05