



4000 Motion 10W-30

Gasoline or Diesel Engine Oil

"Fuel Economy" performance

TYPE OF USE

Specially designed for cars when manufacturers recommend a SAE 10W-30 viscosity oil, low HTHS and fuel economy performances.

Suitable for all types of gasoline engines, with injection and catalytic converter. Suitable for all type of fuel.

These oils may be unsuitable for use in some engines. Refer to the owner manual or handbook if in doubt.

PERFORMANCE

STANDARDS ACEA **A1 / B1**
APPROVALS API SJ / CF

The new performance **ACEA A1/B1** requests fuel economy and low emission performance for engines. MOTUL 4000 Motion 10W-30 reduces friction in the engine.

Detergent, dispersive agents and anti-oxidation additivation are particularly reinforced to resist to longer oil change, required by manufacturers for the new model of cars.

Anti-deposit and anti-black sludge power very efficient which allows to maintain a clean engine.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.

MOTUL 4000 Motion 10W30 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 15°C (59°F)	ASTM D1298	0.871
Viscosity at 100°C (212°F)	ASTM D445	12.1 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	81.0 mm ² /s
Viscosity index	ASTM D2270	145
Pour point	ASTM D97	-27°C / -16°F
Flash point	ASTM D92	220°C / 428°F
TBN	ASTM D 2896	8.8 mg KOH/g