



5100 4T 15W-50

High performance lubricant for bikes

Technosynthese – Ester

TYPE OF USE

Street & road bikes, trails, off road bikes, enduro, trial...fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2 or Euro 3 emission regulation, fitted with exhaust gas after treatment systems : catalytic converters, air injection into exhaust pipe...

Other uses : street bikes without catalytic converters, scooters, ATV, mopeds...

PERFORMANCE

STANDARDS

API SL / SJ / SH / SG

APPROVAL

JASO MA under N° M033MOT057

Protection

Technosynthese lubricant reinforced by Ester base stock to warranty antiwear properties and improve gear protection and life time.

Improved oil film resistance at high temperatures.

Grade 50 at hot temperature, specially designed for big bore engines, thumpers, twins, multicylinders...

Low Phosphorus and Sulphur content for better operating conditions of catalytic converters required to meet last emission regulation.

Comfort

JASO MA approved to warranty a perfect lock up of wet clutch.

Easy gear shifting.

RECOMMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	15W-50
Density at 20°C (68°F)	ASTM D1298	0.878
Viscosity at 40°C (104°F)	ASTM D445	130.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	17.6 mm ² /s
Viscosity index	ASTM D2270	149
Pour point	ASTM D97	-39°C / - 38°F
Flash point	ASTM D92	232°C / 449°F
TBN	ASTM D 2896	8.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Site Web : www.motul.fr

8367

10/05