



8100 X-clean 5W-40

ACEA C3

Gasoline & Diesel lubricant for Euro IV engines

100% Synthetic

TYPE OF USE

Lubricant specially designed for last generation cars, powered by turbo Diesel direct injection or gasoline engines, EURO IV emission regulation compliant, requiring an ACEA C3 engine oil, high HTHS (> 3.5 mPa.s) viscosity and "Mid SAPS" with reduced content of sulphated ash (= 0.8%), phosphorus (0.07 = x = 0.09%) and sulphur (= 0.3%).

Suitable for any type of Diesel or gasoline engines calling for ACEA A3/B3 or A3/B4 lubricants.

ATTENTION : For BMW vehicles, this product can be used for gasoline engines only in European Union countries, Switzerland, Norway and Liechtenstein. Refer to BMW recommendation.

PERFORMANCES

STANDARDS	ACEA A3 / B4 / C3
APPROVALS	API SM / CF
	BMW Long Life 04, MB 229.31, Porsche, VW 502 00 – 505 00
RECOMMENDATIONS	Renault/Nissan – Fiat – Kia – Suzuki – Ssangyong...

Engines compliant with EURO IV emission regulation are fitted with sensitive exhaust gas after treatment systems :

- Sulphur and Phosphorus inhibit catalytic convertors operation and can damage catalytic components : inefficient exhaust gas treatment.
- Sulphated Ashes clog diesel particulate filters : shorten regenerating cycle, higher fuel consumption and engine power loss.

ACEA developed ACEA C3 standard for lubricants with high HTHS (> 3.5 mPa.s), reduced Sulphated Ash, Phosphorus and Sulphur content (Mid SAPS), suitable for use with exhaust gas after treatment systems.

ACEA C3 lubricants achieve extended drain intervals managed by vehicles computer on board.

RECOMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.
Do not mix with lubricants not ACEA C3 compliants.

PROPERTIES

Viscosity grade	SAE J 300	5W-40
Density at 20°C (68°F)	ASTM D1298	0,850
Viscosity at 100°C (212°F)	ASTM D445	13.9 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	83.4 mm ² /s
Viscosity index	ASTM D2270	171
Pour point	ASTM D97	-39°C / -38°F
Flash point	ASTM D92	230°C / 446°F
TBN	ASTM D 2896	7.9 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

8416

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Site Web : www.motul.fr

03/06