



# DEXRON IID

**Automatic gearbox lubricant**

**Power steering system**

**Torque converters and hydraulic systems**

## TYPE OF USE

For all systems when DEXRON II standard is required

Automatic gearboxes and transmissions, torque converters, power steering systems, hydraulic circuits, boat reversing gears...

## PERFORMANCES

APPROVALS	MAN 339D – MB 236.7 – VOITH 55.6335.32 (G607)
	ZF TE ML-03D / 04D / 11A / 14A / 17C
PERFORMANCE	GENERAL MOTOR DEXRON II D
	ALLISON C-4 – CATERPILLAR TO-2

Very high fluidity at low temperatures which allows easy gear changing.  
Thermal stability under high temperature.  
Anti-wear, Anti-corrosion, Anti-foam.

## RECOMMENDATIONS

MOTUL DEXRON II D is the latest progress from DEXRON specification.  
Can be used each time "DEXRON B" specification is recommended.  
Oil change: According to manufacturers' requirements and adjust according to your own use.

## PROPERTIES

Color	Visual	Red
Density at 15°C (59°F)	ASTM D1298	0.868
Viscosity at 40°C (104°F)	ASTM D445	38.5 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	7.8 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	179
Flash point	ASTM D92	224°C / 435°F
Pour point	ASTM D97	< -36°C / < -33°F