



EPL 90

Mechanical transmission lubricant

Extreme pressure

TYPE OF USE

All gearboxes, gearbox/differential and hypoid differentials without limited slip system operating under moderate loads and revolution speed or transfer gearboxes, mechanical transmissions without hypoid gear, reduction gears operating under moderate to severe load and revolution speed.

PERFORMANCES

STANDARDS : API GL4 – MIL-L 2105
PERFORMANCE MAN 341type N, ZF TE-ML 16A / 17A

Extreme pressure lubricant for an efficient anti wear protection.
Very high lubricating properties to reduce friction.
Suitable for any type of seal
Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J 306	90
Density at 15°C (59°F)	ASTM D1298	0.895
Viscosity at 40°C (104°F)	ASTM D445	181.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	16.8 mm ² /s
Viscosity index	ASTM D2270	98
Flash point	ASTM D92	222°C / 431°F
Pour point	ASTM D97	-15°C / 5°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.
Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL- 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - TEL : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site : www.motul.fr

3154

06/03