



MOTUL GARDEN 2T

2 Stroke Engine Lubricant for Motorised Garden Tools

Technosynthèse

API TC

TYPE OF USE

Specially Formulated for 2 Stroke Engine Garden Tools

Motor cultivator, chain saw, lawn mower, ground clearing machine...

Recommended for engines working under severe conditions or at high rating.
Suitable with leaded or unleaded gasoline.

PERFORMANCE

STANDARDS : API TC

Pre-diluted lubricant which mixes instantaneously with gasoline and remains stable.
Reinforced anti-rust and anti-corrosion properties.
Reduces deposits in exhaust pipes and on pistons.
Prevents spark plug from fouling.

RECOMMENDATIONS

Premix ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

PROPERTIES

Technosynthèse lubricant.
Colour the gasoline in red.

| | | |
|----------------------------|------------|-------------------------|
| Density at 15°C (59°F) | ASTM D1298 | 0.873 |
| Viscosity at 40°C (104°F) | ASTM D445 | 66.2 mm ² /s |
| Viscosity at 100°C (212°F) | ASTM D445 | 9.5 mm ² /s |
| Viscosity index | ASTM D2270 | 123 |
| Flash point | ASTM D92 | 108°C / 226°F |