



# MOTUL GARDEN 4T SAE 10W-30

**4 Stroke Engine Lubricant for Motorised Garden Tools**

**Gasoline and Diesel Engine**

**Technosynthèse - SAE 10W-30**

## TYPE OF USE

**Specially Formulated for Motorised Garden Tools and Small Farming Machines  
All Gasoline and Diesel 4 Stroke Engines, naturally aspirated or Turbocharged.**

Lawn mowers, motor mowers, light tractors...

Suitable for all types of fuel: leaded and unleaded gasoline, diesel fuel.

All types of 4 stroke engines with or without catalytic converter.

## PERFORMANCE

**STANDARDS : API SJ - SH / CF**

Reinforced with a synthetic base stock for improved engine protection

Ensures the engine cleanliness

Protection during wintering

Dispersant and detergent properties

Good cold starting, perfectly stable in a hot engine

Anti-oxidation, Anti-wear properties.

Anti-corrosion, Anti-foam properties.

## RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.  
MOTUL GARDEN 4T SAE 10W-30 can be mixed with synthetic or mineral lubricants.

## PROPERTIES

Mineral multigrade lubricant.

Viscosity grade	SAE J 300	<b>10W-30</b>
Density at 15°C (59°F)	ASTM D 1298	0.875
Viscosity at 40°C (104°F)	ASTM D 445	70.3 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D 445	10.6 mm <sup>2</sup> /s
Viscosity index (VIE)	ASTM D 2270	139
Flash point	ASTM D 92	226°C / 439°F
Pour point	ASTM D 97	-30°C / -22°F
TBN	ASTM D 2896	8.0 mg KOH/g