



# MOTUL GARDEN 4T SAE 15W-40

**4 Stroke Engine Lubricant for Motorised Garden Tools**

**Gasoline and Diesel Engine**

**SAE 15W-40**

## TYPE OF USE

**Specially Formulated for Motorised Garden Tools and Small Farming Machines  
All Gasoline and Diesel 4 Stroke Engines, naturally aspirated or Turbocharged.**

Lawn mowers, motor mowers, light tractors...

Suitable for all types of fuel: leaded and unleaded gasoline, diesel fuel.

All types of 4 stroke engines with or without catalytic converter.

## PERFORMANCE

**STANDARDS: API SG / CD - CCMC G-4 / D-4**

Ensures the engine cleanliness

Protection during wintering

Dispersant and detergent properties

Good cold starting, perfectly stable in a hot engine

Anti-oxidation, Anti-wear properties.

Anti-corrosion, Anti-foam properties.

## RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.  
MOTUL GARDEN 4T SAE 15W-40 can be mixed with synthetic or mineral lubricants.

## PROPERTIES

Mineral multigrade lubricant.

Viscosity grade	SAE J 300	<b>15W-40</b>
Density at 15°C (59°F)	ASTM D 1298	0.881
Viscosity at 40°C (104°F)	ASTM D 445	101.3 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D 445	13.7 mm <sup>2</sup> /s
Viscosity index (VIE)	ASTM D 2270	136
Flash point	ASTM D 92	222°C / 432°F
Pour point	ASTM D 97	-30°C / -22°F
TBN	ASTM D 2896	7.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE.

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 - Web Site: [www.motul.com](http://www.motul.com)

8350

04/05