



INBOARD 4T 15W50

Oil for Marine engines

Inboard gasoline 4 stroke

Technosynthèse

TYPE OF USE

Specially designed for gasoline inboard 4 stroke engines.
Gasoline inboard engines : CRUSADER, MERCUISER, VOLVO, YAMAHA...
Suitable for Diesel inboard engines, turbocharged or not.

PERFORMANCES

STANDARDS API SH / SG / CD

Reinforced anti-friction properties by the MOTUL " Technosynthèse " base stock to increase engine life.
Exceeds the API SH standard level for gasoline engines.
High detergency and dispersive properties to prevent deposit formation in the engine.
Reinforced anti-corrosion additivation.
Anti-oxidant, anti-foam.

RECOMMENDATIONS

Oil change : According to manufacturers' recommendations and to be adjusted according to use and oil test results.
MOTUL INBOARD 4T can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J300	15W-50
Density at 15°C (59°F)	ASTM D1298	0.878
Viscosity at 40°C (104°F)	ASTM D445	130 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	17.8 mm ² /s
Viscosity index	ASTM D2270	153
Flash point	ASTM D92	224°C / 435°F
Pour point	ASTM D97	-30°C / -22°F
TBN	ASTM D 2896	8.5 mg KOH/g