



INUGEL OPTIMAL

Ready to use cooling liquid

**Anti-corrosion and anti freeze,
Protection -30°C/-22°F
AOT Technology**

Nitrite free / Amine free / Phosphate free / Borate free / Silicate free

TYPE OF USE

MOTUL INUGEL OPTIMAL is a ready to use cooling liquid, based on monoethyleneglycol, using organic additives (AOT).

Strongly recommended for all cooling systems : passenger cars, heavy duty, construction and agriculture vehicles, gardening, ships, stationary engines ...

PERFORMANCES

STANDARDS AND MANUFACTURER SPECIFICATIONS : Refer to chart.

Contains a bitterness agent to prevent from drinking : coolants and antifreezes have a sweet taste but are harmful.

Cooling system optimal protection from freezing and metallic parts from corrosion.

AOT technology provides an excellent thermal exchange and then engine cooling efficiency and prevents from boiling.

This organic technology provides anti-corrosion properties that remain while high temperature and ageing. Low corrosion inhibitors consumption allows extended drain intervals. Water pump protection, avoid cavitation.

Seals, durits and plastic parts friendly.

RECOMMENDATIONS

Ready to use, do not add any water

Drain intervals : Refer to the manufacturers' recommendation.

Do not mix with non organic products.

This product should not be used to protect drinking water systems against freezing.

PROPERTIES

Nitrite free, amine free, phosphate free, borate free, silicate free.

Color	Visual	Orange fluo
Density at 20°C/68°F	ASTM D4052	1.056
PH	ASTM D1287	8.4
Initial crystalization	ASTM D1177	-27.5°C/-17.5°F
Freezing Protection		-30°C/-22°F
Pour Point	ASTM D97	-32.5°C/-26.5°F
Boiling Temperature		134°C/273°F (+1.5 bar)
Alkalinity Reserve	ASTM D1121	2.4 mg KOH/g

MOTUL INUGEL OPTIMAL

OEM Group	OEM	Spec
Cummins	Cummins	IS Series & N14
Cummins	Cummins/Wärtsilä	32-9011
Daewoo	Daewoo/Ssangyong	
Daimler-Chrysler	Mercedes-Benz	325.3
Detroit Diesel	Detroit Diesel	Powercool Plus
Deutz/MWM	Deutz-MWM	0199-99-1115 / 0199-99-2091
Fiat	Fiat - Lancia	NC 956-16
Fiat	Iveco	18-1830
Ford	Ford/Jaguar	CMR 8229/WSS-M97B44-D
General Motors	Opel - GM - Saab	GM 6277M
General Motors	Vauxhall	QL 130100/GM 6277M
Honda	Honda	HES D 2009-75
Hyundai	Hyundai	
Isuzu	Isuzu	
John Deere	John Deere	JDMH5
Kubota	Kubota	
Komatsu	Komatsu	07.892 (2001)
Leyland-DAF	Leyland Trucks	DW03245403
MAN	MAN/Steyr	324 Typ SNF/MAN 324
MAN B&W	MAN B&W AG	D36 5600
Mazda	Mazda	MEZ 121C
Mitsubishi	Mitsubishi	
MTU	MTU	MTL 5048
Porsche	Porsche	TL-VW 774 D = G 12
PSA	Peugeot Citroën	
Renault	Mack	014GS17009
Renault	Nissan	10120 NDS00
Renault	Renault + RVI	41-01-001/- -Q Type D
Santana Motors	Suzuki	
Scania	Scania	TB 1451/TI 2-98 08 13 TB
Skoda	Liaz	61-0-0257
Volvo	Mack	014 GS 17009
Volvo	Renault Trucks	41-01-001/- -S Type D
Volvo	Volvo	128 6083 / 002
VW	VAG Group	TL-VW 774 D/F = G 12 / G12 +
ASTM Standards		ASTM D3306/D4656/D4985
British Standards		BS 6580
French Standards		NFR 15-601
FVV Standards	Germany	FVV Heft R443
Japanese Standards		JASO M325/JIS K2234
Korean Standards		KSM 2142
MIL Standards	MIL-Belgium	BT-PS-606 A
MIL Standards	MIL-France	DCSEA 615/C
MIL Standards	MIL-Italy	E/L-1415b
MIL Standards	MIL-Sweden	FSD 8704
NATO Standards		NATO S-759
SAE Standards		SAE J1034
UNE Standards		UNE 26-361-88/1

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 – FAX : 33 1 48 33 28 79 – Site Web : www.motul.fr