MOTUL MOLYBDEN

Multipurpose Grease

Lithium – Extreme-Pressure

NLGI 2 – Reinforced with Molybdenum Disulphide

TYPE OF USE

Multipurpose grease specially recommended for civil engineering machinery working in severe conditions : heavy load, repeated shocks, vibrations, presence of water and difficult maintenance.

Greasing of roller bearings, articulations, bearings, hubs, ball joint, cables...

Temperature for use : -30°C / -22°F to +130°C / +266°F

PERFORMANCE

Grease with lithium soap and extreme-pressure, anti-oxidation & anti-corrosion additivation, formulated with a solid lubricant : molybdenum disulphide.

The molybdenum disulphide powder used in that grease is very efficient in boundary conditions and improves the life duration of components working under heavy duty.

Good resistance to water.

Adherent.

Good anti-corrosion and anti-rust protection Very good mechanical stability Good resistance to shearing and vibrations.

Designation DIN 51 502 : KPF 2 K-30

PROPERTIES

Colour	Visual
Consistency grade	DIN 51 818
Soap Penetrability - 60 cycles Drop point	ASTM D217 ASTM D 2265

Anti-corrosion EMCORIP 2200 / 04 ball testASTM D 2596FAG FE-9 TestDIN 51 821

3200 N F50>100h at 130°C

Black NLGI 2 Lithium 265 / 295 x10⁻¹ mm 185°C / 365°F

 We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

 Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.
 Made in FRANCE

 MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – France - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 – Web site : www.motul.com

8041

