



POWERQUAD 10W-40

High performance lubricant for ATVs

100% Synthetic – Ester

TYPE OF USE

Sporty or urban ATVs...fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2 or Euro 3 emission regulation, fitted with exhaust gas after treatment systems : catalytic converters, air injection into exhaust pipe...

ATVs used for leisure.

PERFORMANCE

STANDARDS
APPROVAL

API SL
JASO MA under N° M033MOT068

Protection

Formula reinforced with Ester base stock for its synergy with anti-wear additives and improved shear resistance for improved gear protection and life time.

100% Synthetic lubricant for improved oil film resistance at high temperatures.

Low Phosphorus and Sulphur content for better operating conditions of catalytic converters required to meet last emission regulation.

JASO MA approved to warranty a perfect lock up of wet clutch.
Easy gear shifting.

RECOMMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral lubricants.

PROPERTIES

| | | |
|----------------------------|-------------|-------------------------|
| Colour | Visual | Red |
| Viscosity grade | SAE J 300 | 10W-40 |
| Density at 20°C (68°F) | ASTM D1298 | 0.862 |
| Viscosity at 40°C (104°F) | ASTM D445 | 91 mm ² /s |
| Viscosity at 100°C (212°F) | ASTM D445 | 13.4 mm ² /s |
| Viscosity index | ASTM D2270 | 148 |
| Pour point | ASTM D97 | -36°C / - 32°F |
| Flash point | ASTM D92 | 228°C / 442°F |
| TBN | ASTM D 2896 | 8.1 mg KOH/g |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Site Web : www.motul.fr

8377

07/06