



QUAD 4T 10W-40

Lubricant for 4 stroke ATV, VTT, Quad engine

TYPE OF USE

All 4 stroke ATV, VTT, Quad engine with integrated or separated gearbox used for leisure or professionally. Particularly suitable for wet clutches.

PERFORMANCES

STANDARDS: API SG/SH/CF – JASO MA, approval M033MOT042

JASO MA standard guarantees the perfect working of wet clutch and gearbox longevity.
Formula especially reinforced with extreme pressure additives for gearbox.
High lubricating properties which decrease friction and wear and increase engine lifetime.
High detergent and dispersive properties.
Anti-oxidation, Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: according to manufacturers' requirements and to be adjusted according to particular use.
Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 15°C (59°F)	ASTM D1298	0.875
Viscosity at 40°C (104°F)	ASTM D445	95 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.2 mm ² /s
Viscosity Index	ASTM D2270	154
Flash point	ASTM D92	226°C / 438°F
Pour point	ASTM D97	-33°C / -27°F
TBN	ASTM D 2896	8.5 mg KOH/g