



# Scooter Expert 2T

Oil for 2 stroke engines Scooters

Technosynthese – Anti Smoke

## TYPE OF USE

All scooters daily used in the city.

Suitable for direct injection 2 stroke engines or conventional carburettor.

Can be used with oil injection systems or in premix. Suitable for all type of fuel leaded or unleaded.

Compatible with catalytic converters.

## PERFORMANCES

NORMES

API TC

APPROVALS

JASO FC under N° 033MOT047

Technosynthese engine oil developed for scooter engines running at high rpm, outstanding oil film resistance for anti wear protection.

Avoid deposits and ensure engine cleanliness at all levels : combustion chamber, spark plug, top of the piston, ring grooves, exhaust port, exhaust pipe...

## RECOMMENDATIONS

Mixing ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements and adjust according to your own use.

## PROPERTIES

Colour	Visual	Green
Density à 15°C (59°F)	ASTM D1298	0.861
Viscosity at 100°C (212°F)	ASTM D445	8.0 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)	ASTM D445	45.3 mm <sup>2</sup> /s
Viscosity grade	ASTM D2270	150
Pour Point	ASTM D97	-30°C / -22°F
Flash point	ASTM D92	88°C / 190°F
TBN	ASTM D 2896	0.96 mg KOH/g