



Scooter Expert 4T 10W-40

4 stroke engine oil Scooters and Maxi Scooters

Technosynthèse

TYPE OF USE

Specifically designed for scooters and maxi-scooters fitted with 4 stroke engines, displacement from 50cc to 650cc with or without catalytic converters.

All scooters used downtown in the city.

Suitable for leaded or unleaded fuel.

PERFORMANCES

STANDARDS

API SJ

APPROVALS

JASO MA under N° M033MOT049

Technosynthese oil, reinforced with a synthetic base stock which provides outstanding protection.

JASO MA approval ensure perfect operating conditions when a wet clutch is fitted on the scooter.

Excellent high temperature resistance particularly indicated for city use : full load during long periods and idling at traffic lights.

The SAE 10W-40 viscosity grade corresponds to the most recent manufacturers' recommendations and improves engine starts when cold while lowering wear.

Very low volatility to reduce oil consumption.

Ensure engine cleanliness, detergent and dispersives properties and resistance at viscosity increase due to unburned deposits produced by the engine. Ageing resistance.

Anti-oxidation, Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 15°C (59°F)	ASTM D1298	0.874
Viscosity at 100°C (212°F)	ASTM D445	14.8 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	95.4 mm ² /s
Viscosity index	ASTM D2270	163
Pour point	ASTM D97	-33°C / -27°F
Flash point	ASTM D92	228°C / 442°F
TBN	ASTM D 2896	8.0 mg KOH/g