



SCOOTER GEAR 80W-90

Transmission oil

Extreme pressure

TYPE OF USE

Specially designed for the heavy working conditions of scooters and mopeds transmissions.

Adapted packaging size allowing to carry on the scooter or the moped the required quantity of lubricant for oil top up.

PERFORMANCE

STANDARDS : API GL-4

Very high lubricating power to withstand successive full speed start-ups and stops in city driving conditions.

Oil film thickness remains sufficient in the various driving conditions, idle, sharp accelerations, full power.

Extreme-pressure and anti-wear additives to increase gear set lifetime operating under very high revolutions (short reduction) and shocks during riding (rear wheel lock-up).

Excellent anti-corrosion, anti-oxidation and anti-foam power.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and to be adjusted according to your own use.

PROPERTIES

Viscosity grade	SAE J 306	80W-90
Density at 15°C (59°F)	ASTM D1298	0.887
Viscosity at 40°C (104°F)	ASTM D445	135 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.6 mm ² /s
Viscosity index	ASTM D2270	107
Flash point	ASTM D92	230°C / 446°F
Pour point	ASTM D97	-27°C / 16°F