

# MOTUL SNOWPOWER 2T



**Snowmobile 2 stroke engine lubricant**

**Technosynthese<sup>â</sup> and Anti-Smoke**

**Low pour point : -45°C / -49°F**

## TYPE OF USE

**Specially formulated for snowmobile with 2 stroke engines working under the most extreme weather conditions : polar cold.**

All snowmobile 2 stroke engines with injector systems or lubricated by premix  
All type of use including racing.

## PERFORMANCE

STANDARDS            API TC Low Smoke  
                              Level JASO FC

Low pour point (-45°C) obtained by using a new synthetic base stock and a low amount of solvent that is the solution for easy start up at low temperature.

Low ash formulation lubricant, Ester based with an effective detergent & dispersant power for a perfect piston, chamber and power valves cleanliness.

Mixes instantaneously with gasoline and remains stable.

Reduces frictions and wearing and increases engine life.

Anti-smoke.

## RECOMMENDATIONS

Mixing ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements and adjust according to your own use.

## PROPERTIES

Technosynthese<sup>®</sup> lubricant.

Blue colour.

Density at 15°C (59°F)

ASTM D1298

0,866

Viscosity at 100°C (212°F)

ASTM D445

7,0 mm<sup>2</sup>/s

Viscosity at 40°C (104°F)

ASTM D445

39,0 mm<sup>2</sup>/s

Viscosity index

ASTM D2270

140

Flash point

ASTM D92

115°C / 239°F

Pour point

ASTM D97

- 45°C / - 49°F