

# 100% Synthetic – Ester Based

# TYPE OF USE

**Specially designed for powerful 4 stroke engine snowmobiles :** Yamaha, Skidoo, Artic Cat, Lynx... Strongly recommended for racing.

Suitable for leaded or unleaded gasoline, winter or regular fuel and catalytic converters.

## PERFORMANCE

STANDARDS API SJ

This 100% synthetic engine oil is formulated and developed to meet the most stringent requirements, specially powerful engines :

- Faster rev raisings and maximum power output.
- Outstanding engine protection at high rpm and high temperature.
- Balanced engine operating temperature.
- Easy start in polar cold.
- Avoid starter clutch sliding.

Tested in Canada, Motul Snowpower 4T 0W-40 exceeds factory requirements for 4 stroke engines.

### RECOMMENDATION

Drain interval : refer to manufacturers' recommendations and tune to your own use. MOTUL Snowpower 4T 0W-40 can be mixed with synthetic or mineral oils.

### **PROPERTIES**

Viscosity grade	SAE J 300	0W-40
Density at 15°C (59°F)	ASTM D1298	0.859
Viscosity at 100°C (212°F)	ASTM D445	13 mm²/s
Viscosity at 40°C (104°F)	ASTM D445	72 mm²/s
Viscosity index	ASTM D2270	185
Pour point	ASTM D97	-60°C / -76°F
Flash point	ASTM D92	226°C / 438°F
TBN	ASTM D 2896	10.6 mg KOH/g