



Specific LL A/B 025 5W-30

Gasoline and Diesel engine oil

100% Synthetic

TYPE OF USE

Specifically designed for OPEL, GM and SAAB models fitted with gasoline or turbo diesel direct injection engines, including Y22DTR and Y20DTH engines with catalytic converters. Also suitable for any engine calling for API SL/CF, ACEA A3/B3 or A3/B4 lubricant. Suitable for any type of fuel leaded or unleaded gasoline, Diesel fuels and LPG.

PERFORMANCES

STANDARDS API SL / CF – ACEA A3 / B4
APPROVALS OPEL/GM Gasoline LL A-025 and Diesel LL B-025

- Formulation specially developed for last generation OPEL/GM engines allowing, at the same time, outstanding lubrication (high HTHS > 3.5 mPa.s) and fuel economy
- Minimize oil consumption, low volatility
- Environment friendly and engine protection
- Particularly recommended for last generation engines OPEL 2.0 and 2.2 DTI engines with extended and flexible drain intervals : computer on board.
- Anti oxidant, anti-foam, anti-rust, anti-corrosion

RECOMMENDATION

Drain interval : refer to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.857
Viscosity at 100°C (212°F)	ASTM D445	11.7 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	68.7 mm ² /s
Viscosity index	ASTM D2270	166
Pour point	ASTM D97	-39°C / -38°F
Flash point	ASTM D92	230°C / 446°F
TBN	ASTM D 2896	10.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

8358

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Site Web : www.motul.fr

02/06