



TP/AGRI GREASE

**Multipurpose Grease for Civil engineering
Machinery and Agriculture**

Lithium – Very adherent & resistant to water

NLGI 2 - Extreme-pressure

TYPE OF USE

Multipurpose grease specially formulated for applications requiring a good resistance to heavy loads and to water which are conditions encountered in Civil Engineering and Agriculture.

Greasing of roller bearings, articulations, bearings, cables...

Tractors, Combine (Harvester), wine machinery and all kind of civil engineering machinery.

Temperature for use : -30°C / -22°F to +140°C / +284°F

PERFORMANCE

Grease with lithium soap reinforced by adhesive polymers and with extreme-pressure, anti-oxidation & anti-corrosion additivation.

Advantages :

Excellent results in presence of water

Good adherence on surfaces

Very good anti-wear & anti-corrosion protection

Good performance in time

Excellent results for heavy loads

Designation DIN 51 502: KP 2 N-30

PROPERTIES

Colour	Visual	Green
Consistency grade	DIN 51 818	NLGI 2
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	265 / 295 x10 ⁻¹ mm
Drop point	ASTM D 2265	190°C / 374°F
Anti-corrosion EMCOR	IP 220	0 / 0
TIMKEN Test - load	ASTM D 2509	50 lb
FAG FE-9 Test	DIN 51 821	F50>200h at 140°C