
MOTUL TECH GREASE 300



Semi-synthetic – Complex Lithium NLGI 2 – Extreme-Pressure



TYPE OF USE

Very high performance multipurpose grease

Greasing of roller bearings, articulations, bearings, hubs, cardan joints, ball joint, cables... Suitable with all types of machinery working under normal or severe conditions. Car, Motorbike, Marine, Transport, Civil engineering machinery, industry and farm machines... Particularly efficient in most extreme conditions: high temperature, heavy load, humidity, vibrations and/or long duration of use.

Temperatures for use : from - 30° C / - 22° F to + 150° C / + 302° F in continuous and up to +200°C / +392°F in peak.

PERFORMANCE

Multipurpose grease par excellence, formulated from mineral and synthetic base oil stocks and from a complex lithium soap, with extreme-pressure, anti-wear, anti-oxidation and anti-corrosion additivation.

ADVANTAGES OF MOTUL TECH GREASE 300:

- Excellent performances at high temperature: the drop point higher than 260°C / 500°F allows a continuous use until 150°C / 305°F and punctually at 220°C / 392°F, far higher than classic greases.
- Longer life duration compared to a classic lithium grease.
- Excellent cold properties: pumpability at –30°C / -22°F
- Resistance to heavy loads thanks to its complete high performance extreme-pressure and anti-wear additivation.
- Very high resistance to water, corrosion and rust.
- Reinforced adherence

Security and reduction of maintenance costs.

Designation : DIN 51 502 : KP 2 P-30

PROPERTIES

Colour Visual Green
Consistency grade DIN 51 818 NLGI 2
Soap Complex Lithium
Penetrability - 60 cycles ASTM D217 265 / 295 x10⁻¹ mm
Drop point ASTM D 2265 > 260°C / > 500°F

Anti-corrosion EMCOR IP 2200/0

TIMKEN Test - load ASTM D 2509 50 lb FAG FE-9 Test DIN 51 821 F50>100h at 150°C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – France - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 – Web site : www.motul.com

8035