



TEKMA DIESEL 2T

Lubricant for 2 Stroke Diesel Engine

Turbocharged or Atmospheric

SAE 40

TYPE OF USE

All Diesel Engines Turbocharged or Atmospheric
Specially formulated for DETROIT 2 STROKE DIESEL engines which require API Standards CF-2 or CD II.

All Diesel engines : Trucks, Bulldozers, Construction machinery, Generators, Buses, Farm machinery, Boat engines...

PERFORMANCES

STANDARDS API CF / CF-2.
SPECIFICATIONS MIL-L-2104 D

DIESEL DETROIT industrial 2 stroke engines are specific engines mainly used for construction machinery, generators and boats.

These engines do not bear easily oils with high sulphated ash and justify a specific API CD II standard. TEKMA DIESEL 2T has a sulphated ash content below 1% to meet this use.

Very high anti wear properties which increase life of engines.
Anti-oxidizing, Anti-corrosion, Anti-rust, Anti-foam.

PROPERTIES

Viscosity grade	SAE	40
Density at 15°C (59°F)	ASTM D1298	0.885
Viscosity at 40°C (104°F)	ASTM D445	146.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm ² /s
Viscosity index VIE	ASTM D2270	102
Flash point	ASTM D92	238 °C / 460 °F
Pour point	ASTM D97	-21 °C / -6 °F
Sulphated ash	ASTM D874	0.81 % weight
TBN	ASTM D2896	6.3 mg KOH/g