



TEKMA SUPRA 15W-40

Lubricant for Diesel engine

Naturally aspirated or Turbocharged

TYPE OF USE

All Diesel engines naturally aspirated or Turbocharged which meet EURO II particulate emission limits or not:

Trucks, Bulldozers, Construction machinery, Buses, Farm machinery, stationary engines...

Can be used as single lubricant in case of fleet composed of new & old generation engines.

PERFORMANCES

STANDARDS : ACEA E2, API CG-4

APPROVALS : MACK EO-L, MAN 271, MERCEDES-BENZ page 228.1, MTU Type I, VOLVO VDS, RVI E2 R

Ensures engine protection and longevity :

- dispersant and anti-oxidation properties : protection against soot build up and oil filter plugging.
 - very high Anti-Wear level : bore polishing protection.
 - very high detergent level : piston cleanliness and piston groove deposits control.
- Anti-corrosion, Anti-rust, Anti-foam.

RECOMMENDATIONS

Drain interval : refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J300	15W-40
Density at 15°C (59°F)	ASTM D1298	0.884
Viscosity at 40°C (104°F)	ASTM D445	115.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.6 mm ² /s
Viscosity index	ASTM D2270	129
Flash point	ASTM D92	231°C / 448°F
Pour point	ASTM D97	-30°C / -22°F
TBN	ASTM D2896	10.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. - Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Site Web : www.motul.fr

3221

11/03