



# TRANSOIL 10W-30

Lubricant for gearboxes with wet clutch

## TYPE OF USE

Specially formulated for gearboxes with wet clutch using a different oil from engine oil : gearbox case separated from engine crankcase.

All Motorbikes, Road, Trails, Cross (2 or 4 stroke engine), Enduro (2 or 4 stroke engine), Mopeds, Scooters, Quads...

Suitable when manufacturers require SAE 10W-30 engine oil or SAE 80 gearbox oil.

## PERFORMANCE

STANDARDS:                    API GL4

Gear change very easy.

High resistance oil film between gears.

Avoid clutch slipping for a better efficiency.

Dispersant properties to maintain the clutch clean.

Extreme pressure, Anti-wear, Anti-corrosion, Anti-foam.

## RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

## PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 15°C (59°F)	ASTM D1298	0.875
Viscosity at 100°C (212°F)	ASTM D445	12.4 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)	ASTM D445	78.6 mm <sup>2</sup> /s
Viscosity index VIE	ASTM D2270	148
Flash point	ASTM D92	224°C / 435°F
Pour point	ASTM D97	-30°C / -22°F