

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system323, 1.31987 to 1989

Type		B3. SOHC
Capacity (cm³) / number of cylinders		1324 / 4
Compression ratio / pressure	bar	9.4 / ≥9.7
Oil pressure	bar	[3.5 to 4.4]
Oil temperature	°C	—
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	82
Radiator cap pressure	bar	0.76 to 1.04

Fuel system323, 1.31987 to 1989

Idle speed - manual [auto]	rpm	850±50
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	1.0 to 2.0
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Aisan
Type / ref		28-32 2V Downdraught
Main jet / needle		91, 156
Injection pressure	bar	—
Pump pressure	bar	0.28 to 0.35
Octane rating	RON	91[E 91 RON]

Ignition system323, 1.31987 to 1989

Type		Electronic ¹
Ignition coil		—
Primary resistance	ohms	3.1
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		—
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		—
Ignition timing - basic [static	° Crankshaft @ rpm	2±1 BTDC @ idle
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	0 @ 1200
	° Crankshaft @ rpm	20 @ 3500
	° Crankshaft @ rpm	26 @ 5500
Vacuum range check	mbar	240 to 640
Maximum vacuum advance	° Crankshaft	14
Spark plugs		NGK/Champion
Type		BPR6ES / RN9YC
Electrode gap	mm	0.75 to 0.85

Electrical system323, 1.31987 to 1989

Battery	V / CC / RC	12 / 150 / 55
Alternator voltage / full load current / engine rpm		14.1 to 14.7 / _ / 2500
Starter motor current / voltage - cranking	A / V	60 / 11.5 (no load)
- locked	A / V	—

Running gear323, 1.31987 to 1989

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	1.0

Tyres		
Saloon	Size	155x13: 175/70x13
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	1.8 / 1.8
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	+2.0±3.0
Camber		+49’±30’
Castor		+2°9’±45’
King pin inclination		+12°22’

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	+2.0±3.0
Camber		—

Torque wrench settings323, 1.31987 to 1989

Cylinder head - stage 1	Nm	76 to 81
- stage 2	Nm	—
Cylinder head - stage 3	Nm	—
- stage 4	Nm	—
Big-end bearings	Nm	29 to 34
Main bearings	Nm	54 to 59
Clutch cover	Nm	18 to 26
Flywheel [driveplate]	Nm	96 to 103
Front hubs	Nm	WSM
Rear hubs	Nm	—
Wheel nuts / bolts	Nm	118
Spark plugs	Nm	15 to 23


Capacities323, 1.31987 to 1989

Engine oil & filter	litres	3.3
Gearbox - 4-speed [5-speed]	litres	3.2
Automatic transmission - refill	litres	—
Final drive	litres	WT
Cooling system	litres	5.0
Fuel tank	litres	48


Notes and Illustrations

¹HEI type


1: Idle speed 2: CO / Mixture



1324 cm³, 8V, fwd



1324 cm³, fwd



Aisan 28-32, SOHC 8V