


# Engine Removal/Installation

## Additional Torque Specifications:

### SIDE TRANSMISSION MOUNT AND BRACKET

10 x 1.25 mm  
39 N·m (3.9kg-m, 28 lb-ft)

M/T:




12 x 1.25 mm  
60 N·m (6.0kg-m, 43 lb-ft)

A/T:

12 x 1.25 mm  
55 N·m (5.5kg-m, 40 lb-ft)

10 x 1.25 mm  
39 N·m (3.9kg-m, 28 N·m)

12 x 1.25 mm  
60 N·m (6.0kg-m, 43 lb-ft)



12 x 1.25 mm  
60 N·m (6.0kg-m, 43 lb-ft)

### REAR MOUNT AND BRACKET

10 x 1.25 mm  
55 N·m (5.5 kg-m,  
40 lb-ft)

M/T:

BRACKET

STAY

SPECIAL BOLT  
Replace.

12 x 1.25 mm  
75 N·m (7.5 kg-m,  
54 lb-ft)


SPECIAL BOLT

Replace

12 x 1.25 mm  
75 N·m (7.5 kg-m,  
54 lb-ft)


SPECIAL BOLT Replace  
12 x 1.25 mm  
60 N·m (6.0 kg-m,  
43 lb-ft)

REAR MOUNT



A/T:

12 x 1.25 mm  
55 N·m (5.5kg-m, 40 lb-ft)




SPECIAL BOLT Replace

12 x 1.25 mm  
60 N·m (6.0kg-m, 43 lb-ft)

10 x 1.25 mm  
47 N·m (4.7kg-m,  
34 lb-ft)

REAR  
MOUNT



10 x 1.25 mm  
55 N·m (5.5kg-m,  
40 lb-ft)




SPECIAL BOLT  
Replace

12 x 1.25 mm  
60 N·m (6.0kg-m, 43 lb-ft)

FRONT  
MOUNT



REAR BEAM



FRONT BEAM


SPECIAL BOLT  
Replace

12 x 1.25 mm  
68 N·m (6.8kg-m, 45 lb-ft)

SPECIAL BOLT  
Replace

12 x 1.25 mm  
68 N·m (6.8kg-m, 45 lb-ft)

12 x 1.25 mm  
75 N·m (7.5kg-m,  
54 lb-ft)



ENGINE SIDE  
MOUNT

12 x 1.25 mm  
55 N·m (5.5kg-m, 40 lb-ft)