

DRIVE BELT ADJUSTMENT SPECIFICATIONS

Article Text

1993 Honda Prelude

For Cadi Centre Nsk CA 95051

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, July 08, 2001 11:26AM

ARTICLE BEGINNING

1993 ENGINE COOLING

Honda Motors Drive Belt Adjustment Specifications

Honda; Prelude

NOTE: For water pump removal procedure, see 2.2L 4-CYL & 2.3L 4-CYL article in ENGINES.

BELT ADJUSTMENT SPECIFICATIONS

BELT ADJUSTMENT TABLE

AA

Application	(1) Deflection In. (mm)
-------------	----------------------------

A/C Compressor

New	13/32-31/64 (10.0-12.0)
-----------	-------------------------

Used	3/16-9/32 (4.5-7.0)
------------	---------------------

Alternator

New

With A/C	7/32-19/64 (5.5-7.5)
----------------	----------------------

Without A/C	5/16-31/64 (8.0-10.0)
-------------------	-----------------------

Used

With A/C	13/32-31/64 (10.0-12.0)
----------------	-------------------------

Without A/C	25/64-1/2 (10.5-12.5)
-------------------	-----------------------

Power Steering

New	3/8-29/64 (9.5-11.5)
-----------	----------------------

Used	17/32-21/32 (13.5-16.5)
------------	-------------------------

(1) - Deflection is with 22 lbs. (10 kg) pressure applied
midway on longest belt run.

AA

END OF ARTICLE