## SS0FE-09

## **TORQUE SPECIFICATION**

Part tighten	N·m	kgf⋅cm	ft·lbf
FRONT SUSPENSION			_
ABS speed sensor wire harness x Shock absorber	5.0	51	44 in.·lbf
Height control sensor link x Bracket	5.4	55	48 in.·lbf
Stabilizer bar x Stabilizer bar link	49	500	36
Shock absorber x Shock absorber bracket	64	650	47
Piston rod x Suspension support	34	350	25
Suspension support x Body	35	360	26
Upper suspension arm x Body	59	600	44
REAR DRIVE SHAFT			
Exhaust tail pipe x Exhaust center pipe	43	440	32
Rear suspention member brace x Body	50	510	37
Drive shaft x Axle hub	289	2,950	213
Drive shaft x Differential side gear shaft	68	695	50
REAR DIFFERENTIAL			
Differential drain plug	49	500	36
Differential filler plug	49	500	36
Differential mounting bolt Front	95	970	70
Rear	142	1,450	105
Ring gear set bolt	97	985	71
Companion flange lock nut	See page SA-56		
Differential carrier cover set bolt	47	475	34
Breather plug	21	210	15
Rear suspension member brace set bolt	50	510	37
Front exhaust pipe x Exhaust pipe assembly	62	632	46
Heated oxygen sensor	44	450	33
Propeller shaft center support bearing set bolt	49	500	36
Propeller shaft assembly x Rear differential	74	750	54
Differential carrier x Bearing cap	85	870	63
Oil deflector x Differential carrier cover	8.0	82	71 in.·lbf
Rear suspension member x Body	127	1,300	94
Rear suspension member stopper x Body	19	195	14
Rear suspension member lower brace x Body	19	195	14
Parking brake cable x Body	7.8	80	69 in.·lbf
REAR SUSPENSION			
Suspension support x Body Upper side	64	650	47
Lower side	18	185	13
Piston rod x Suspension support	28	280	21
Upper suspension arm x Body Front side	88	900	65
Rear side	74	755	55
No. 2 lower suspension arm x Stabilizer bar link	30	305	22
No. 2 lower suspension arm x Shock absorber	110	1,120	81
No. 2 lower suspension arm x Rear suspension member	110	1,120	81
Height control sensor link x Bracket	5.4	55	48 in.·lbf
Toe control link x Rear suspension member	49	500	36