

PROPELLER SHAFT

SERVICE DATA

Propeller shaft assembly swing	Maximum: 0.8 mm (0.031 in.)
Propeller shaft assembly rear swing	Maximum: 0.8 mm (0.031 in.)
Intermediate shaft runout	Maximum: 0.8 mm (0.031 in.)
Intermediate shaft front flange runout	Maximum: 0.1 mm (0.004 in.)
Intermediate shaft rear flange runout (horizontal direction)	Maximum: 0.1 mm (0.004 in.)
Intermediate shaft rear flange runout (vertical direction)	Maximum: 0.1 mm (0.004 in.)

SS

TORQUE SPECIFICATIONS

Part Tightened	N*m	kgf*cm	ft.*lbf
Intermediate shaft x Center support bearing assembly No. 1 (front) 1st	182	1,850	134
Intermediate shaft x Center support bearing assembly No. 1 (front) Loosen nut			
Intermediate shaft x Center support bearing assembly No. 1 (front) 2nd	69	700	51
Intermediate shaft x Center support bearing assembly No. 1 (rear) 1st	182	1,850	134
Intermediate shaft x Center support bearing assembly No. 1 (rear) Loosen nut			
Intermediate shaft x Center support bearing assembly No. 1 (rear) 2nd	69	700	51
Propeller shaft assembly x Front flange	74	750	54
Propeller shaft assembly rear x Rear differential	74	750	54
Intermediate shaft rear flange x Propeller shaft assembly rear	29	296	21
Center support bearing assembly No. 1 (front) x Body	37	375	27
Center support bearing assembly No. 1 (rear) x Body	37	375	27

SS