
GROUP 31

WHEEL AND TYRE

CONTENTS

GENERAL INFORMATION 31-2

GENERAL INFORMATION

M2310000100275

ROAD WHEEL AND TYRE

The wheels and tyres of the following specifications have been established.

ROAD WHEEL AND TYRE

Item		1100	1300	1500
Wheel	Type	Steel type Aluminium type*	Steel type Aluminium type*	Steel type Aluminium type*
	Size	14 × 5.5J 15 × 6J*	14 × 5.5J 15 × 6JJ* 16 × 6.5*	15 × 6J 16 × 6.5J*
	Amount of wheel offset (mm)	46	46	46
	PCD (mm)	114.3	114.3	114.3
Tyre	Size	175/65R14 82T 195/50R15 82H*	175/65R14 82T 195/50R15 82H* 205/45R16 83H*	195/50R15 82H* 205/45R16 83H*

NOTE: The * mark indicates optional item.

NOTE: PCD (Pitch Circle Diameter) indicates the pitch circle diameter of the wheel installation holes.

SPARE WHEEL AND TYRE OR TYRE
REPAIR KIT

The spare wheel and tyre and the tyre repair kit have been established as options.

SPARE WHEEL AND TYRE (OPTION)

Item		Specifications
Spare wheel	Type	Steel type
	Size	15 × 4T
	Amount of wheel offset (mm)	46
	PCD (mm)	114.3
Spare tyre	Size	T115/70D15

NOTE: PCD (Pitch Circle Diameter) indicates the pitch circle diameter of the wheel installation holes.

TYRE REPAIR KIT (OPTION)

The tyre repair kit is established for easy emergency-fixing of flat tyres.

- The tyre repair kit consists of the repair set and the tyre compressor, and is installed on the luggage room.
- The repair set consists of the bottle of sealant, the hose, and the valve remover.

- The power of compressor is exclusive to the cigarette lighter (DC 12 V).
- The compact kit weighs less than a spare tyre resulting in the effective space use.
- Before the tyre for which the tyre repair kit was used is repaired or replaced, the repair agent remaining inside the tyre must be removed.
- When the hole of the flat tyre can be identified, the flat tyre can be repaired ordinarily. Otherwise, replace the tyre with a new one.