GROUP 31

WHEEL AND TIRE

CONTENTS

GENERAL INFORMATION	31-2	TIRE PRESSURE MONITORING SYSTEM	
		(TPMS)	31-2

GENERAL INFORMATION

M2310000100941

- The wheels and tires of the following specifications have been established.
- Adopt the Tire Pressure Monitoring System (TPMS).
 - Warns driver of low tire pressure by illuminating the TPMS warning light on the combination meter.
- Warns driver of TPMS probrems by flashing^{*} the TPMS warning light on the combination meter.

NOTE: *: Change to continuous illumination after flashing for about 1 minute.

SPECIFICATIONS

ROAD WHEEL AND TIRE

Item		DE	ES	GTS
TPMS warning pressure kPa (psi)	Warning ON	174 (25.2) or less	174 (25.2) or less	174 (25.2) or less
	Warning OFF	189 (27.4) or less	189 (27.4) or less	189 (27.4) or less
Wheel Type Size Amount of wheel offset mm (in) PCD mm (in)	Туре	Steel type or Aluminium type*	Aluminum type	Aluminum type
	Size	16 × 6 1/2JJ	16 × 6 1/2JJ	18 × 7JJ
	Amount of wheel offset mm (in)	46 (1.8)	46 (1.8)	46 (1.8)
	PCD mm (in)	114.3 (4.50)	114.3 (4.50)	114.3 (4.50)
Tire	Size	P205/60R16 91H	P205/60R16 91H	P215/45R18 89V

SPARE WHEEL AND TIRE

Item		Specification	
Wheel	Туре	Steel type	
	Size	16 × 4T	
	Amount of wheel offset mm (in)	40 (1.6)	
	PCD mm (in)	114.3 (4.50)	
Tire	Size	T125/70D16 96M	

NOTE:

- The * mark indicates optional item.
- PCD indicates the pitch circle diameter of the wheel installation holes.

TIRE PRESSURE MONITORING SYSTEM (TPMS)

M2310000200067

Refer to GROUP 42B –Keyless Operation System (KOS) P.42B-20 or GROUP 42C –Wireless Control Module (WCM) P.42C-9.