

WHEEL AND TYRE

E9DMAAB

On the wide fender equipped vehicles, aluminum wheels are standard equipment. The offset amount of wheel, reduced for the wider

fender installation, have contributed to wider track and better cornering performance.

SPECIFICATIONS

<Vehicles for Europe>

Items	Vehicles with wide fender	Vehicles without wide fender
Wheel		
Type	Aluminum type	Steel type Aluminum type* ¹
Size	15 x 7JJ	15 x 6JJ
Offset	mm (in.) 10 (0.39)	33 (1.29)
Pitch circle diameter	mm (in.) 139.7 (5.5)	139.7 (5.5)
Tyre		
Size	265/70R15 110S	235/75R15 105S 215R15 100S* ¹
Tyre inflation pressure	kPa (kg/cm ² , psi)	
When 4 passengers		
Front	180 (1.8, 26)	180 (1.8, 26)
Rear	200 (2.0, 28)	200 (2.0, 28) 210 (2.1, 30)* ²
When 4 passengers to max. load or trailer towing		
Front	180 (1.8, 26)	180 (1.8, 26)
Rear	200 (2.0, 28)	220 (2.2, 31) 230 (2.3, 33)* ²

NOTE

*¹: Optional equipment

*²: Tire inflation pressure for optional tyres