

Edition: December 2002  
Revision: April 2004



**FX35/FX45**

**MODEL S50 SERIES**



**INFINITI**

©2004 NISSAN MOTOR CO., LTD.

**QUICK REFERENCE INDEX**

<b>A GENERAL INFORMATION</b>	GI General Information	
<b>B ENGINE</b>	EM Engine Mechanical	
	LU Engine Lubrication System	
	CO Engine Cooling System	
	EC Engine Control System	
	FL Fuel System	
	EX Exhaust System	
	ACC Accelerator Control System	
	AT Automatic Transmission	
<b>C TRANSMISSION/ TRANSAXLE</b>		
<b>D DRIVELINE/AXLE</b>	TF Transfer	
	PR Propeller Shaft	
	FFD Front Final Drive	
	RFD Rear Final Drive	
	FAX Front Axle	
	RAX Rear Axle	
	FSU Front Suspension	
	RSU Rear Suspension	
<b>E SUSPENSION</b>	WT Road Wheels & Tires	
	BR Brake System	
	PB Parking Brake System	
<b>F BRAKES</b>	BRC Brake Control System	
	PS Power Steering System	
	SB Seat Belts	
<b>G STEERING</b>	SRS Supplemental Restraint System (SRS)	
<b>H RESTRAINTS</b>	BL Body, Lock & Security System	
<b>I BODY</b>	GW Glasses, Window System & Mirrors	
	RF Roof	
	EI Exterior & Interior	
	IP Instrument Panel	
	SE Seat	
	ATC Automatic Air Conditioner	
	SC Starting & Charging System	
<b>J AIR CONDITIONER</b>	LT Lighting System	
	DI Driver Information System	
	WW Wiper, Washer & Horn	
	BCS Body Control System	
	LAN LAN System	
	AV Audio, Visual, Navigation & Telephone System	
	ACS Auto Cruise Control System	
	PG Power Supply, Ground & Circuit Elements	
	MA Maintenance	
	<b>K ELECTRICAL</b>	IDX Alphabetical Index
<b>L MAINTENANCE</b>		
<b>M INDEX</b>		

**A**  
**B**  
**C**  
**D**  
**E**  
**F**  
**G**  
**H**  
**I**  
**J**  
**K**  
**L**  
**M**

## INCH TO METRIC CONVERSION TABLE

(Rounded-off for automotive use)

inches	mm	inches	mm
.100	<b>2.54</b>	.610	<b>15.49</b>
.110	<b>2.79</b>	.620	<b>15.75</b>
.120	<b>3.05</b>	.630	<b>16.00</b>
.130	<b>3.30</b>	.640	<b>16.26</b>
.140	<b>3.56</b>	.650	<b>16.51</b>
.150	<b>3.81</b>	.660	<b>16.76</b>
.160	<b>4.06</b>	.670	<b>17.02</b>
.170	<b>4.32</b>	.680	<b>17.27</b>
.180	<b>4.57</b>	.690	<b>17.53</b>
.190	<b>4.83</b>	.700	<b>17.78</b>
.200	<b>5.08</b>	.710	<b>18.03</b>
.210	<b>5.33</b>	.720	<b>18.29</b>
.220	<b>5.59</b>	.730	<b>18.54</b>
.230	<b>5.84</b>	.740	<b>18.80</b>
.240	<b>6.10</b>	.750	<b>19.05</b>
.250	<b>6.35</b>	.760	<b>19.30</b>
.260	<b>6.60</b>	.770	<b>19.56</b>
.270	<b>6.86</b>	.780	<b>19.81</b>
.280	<b>7.11</b>	.790	<b>20.07</b>
.290	<b>7.37</b>	.800	<b>20.32</b>
.300	<b>7.62</b>	.810	<b>20.57</b>
.310	<b>7.87</b>	.820	<b>20.83</b>
.320	<b>8.13</b>	.830	<b>21.08</b>
.330	<b>8.38</b>	.840	<b>21.34</b>
.340	<b>8.64</b>	.850	<b>21.59</b>
.350	<b>8.89</b>	.860	<b>21.84</b>
.360	<b>9.14</b>	.870	<b>22.10</b>
.370	<b>9.40</b>	.880	<b>22.35</b>
.380	<b>9.65</b>	.890	<b>22.61</b>
.390	<b>9.91</b>	.900	<b>22.86</b>
.400	<b>10.16</b>	.910	<b>23.11</b>
.410	<b>10.41</b>	.920	<b>23.37</b>
.420	<b>10.67</b>	.930	<b>23.62</b>
.430	<b>10.92</b>	.940	<b>23.88</b>
.440	<b>11.18</b>	.950	<b>24.13</b>
.450	<b>11.43</b>	.960	<b>24.38</b>
.460	<b>11.68</b>	.970	<b>24.64</b>
.470	<b>11.94</b>	.980	<b>24.89</b>
.480	<b>12.19</b>	.990	<b>25.15</b>
.490	<b>12.45</b>	1.000	<b>25.40</b>
.500	<b>12.70</b>	2.000	<b>50.80</b>
.510	<b>12.95</b>	3.000	<b>76.20</b>
.520	<b>13.21</b>	4.000	<b>101.60</b>
.530	<b>13.46</b>	5.000	<b>127.00</b>
.540	<b>13.72</b>	6.000	<b>152.40</b>
.550	<b>13.97</b>	7.000	<b>177.80</b>
.560	<b>14.22</b>	8.000	<b>203.20</b>
.570	<b>14.48</b>	9.000	<b>228.60</b>
.580	<b>14.73</b>	10.000	<b>254.00</b>
.590	<b>14.99</b>	20.000	<b>508.00</b>
.600	<b>15.24</b>		

## METRIC TO INCH CONVERSION TABLE

(Rounded-off for automotive use)

mm	inches	mm	inches
<b>1</b>	.0394	<b>51</b>	2.008
<b>2</b>	.079	<b>52</b>	2.047
<b>3</b>	.118	<b>53</b>	2.087
<b>4</b>	.157	<b>54</b>	2.126
<b>5</b>	.197	<b>55</b>	2.165
<b>6</b>	.236	<b>56</b>	2.205
<b>7</b>	.276	<b>57</b>	2.244
<b>8</b>	.315	<b>58</b>	2.283
<b>9</b>	.354	<b>59</b>	2.323
<b>10</b>	.394	<b>60</b>	2.362
<b>11</b>	.433	<b>61</b>	2.402
<b>12</b>	.472	<b>62</b>	2.441
<b>13</b>	.512	<b>63</b>	2.480
<b>14</b>	.551	<b>64</b>	2.520
<b>15</b>	.591	<b>65</b>	2.559
<b>16</b>	.630	<b>66</b>	2.598
<b>17</b>	.669	<b>67</b>	2.638
<b>18</b>	.709	<b>68</b>	2.677
<b>19</b>	.748	<b>69</b>	2.717
<b>20</b>	.787	<b>70</b>	2.756
<b>21</b>	.827	<b>71</b>	2.795
<b>22</b>	.866	<b>72</b>	2.835
<b>23</b>	.906	<b>73</b>	2.874
<b>24</b>	.945	<b>74</b>	2.913
<b>25</b>	.984	<b>75</b>	2.953
<b>26</b>	1.024	<b>76</b>	2.992
<b>27</b>	1.063	<b>77</b>	3.031
<b>28</b>	1.102	<b>78</b>	3.071
<b>29</b>	1.142	<b>79</b>	3.110
<b>30</b>	1.181	<b>80</b>	3.150
<b>31</b>	1.220	<b>81</b>	3.189
<b>32</b>	1.260	<b>82</b>	3.228
<b>33</b>	1.299	<b>83</b>	3.268
<b>34</b>	1.339	<b>84</b>	3.307
<b>35</b>	1.378	<b>85</b>	3.346
<b>36</b>	1.417	<b>86</b>	3.386
<b>37</b>	1.457	<b>87</b>	3.425
<b>38</b>	1.496	<b>88</b>	3.465
<b>39</b>	1.535	<b>89</b>	3.504
<b>40</b>	1.575	<b>90</b>	3.543
<b>41</b>	1.614	<b>91</b>	3.583
<b>42</b>	1.654	<b>92</b>	3.622
<b>43</b>	1.693	<b>93</b>	3.661
<b>44</b>	1.732	<b>94</b>	3.701
<b>45</b>	1.772	<b>95</b>	3.740
<b>46</b>	1.811	<b>96</b>	3.780
<b>47</b>	1.850	<b>97</b>	3.819
<b>48</b>	1.890	<b>98</b>	3.858
<b>49</b>	1.929	<b>99</b>	3.898
<b>50</b>	1.969	<b>100</b>	3.937

QUICK REFERENCE CHART FX35/FX45

PFP:00000

ENGINE TUNE-UP DATA (VQ35DE)

ELS0003W

Engine model		VQ35DE				
Firing order		1-2-3-4-5-6				
Idle speed A/T (In "P" or "N" position)	rpm	650±50				
Ignition timing (BTDC at idle speed) A/T (In "P" or "N" position)		15°± 5°				
CO% at idle		0.7 - 9.9 % and engine runs smoothly				
Drive Belt	Deflection adjustment		Unit: mm (in)	Tension adjustment		Unit: N (kg, lb)
	Used belt		New belt	Used belt		New belt
	Limit	After adjustment		Limit	After adjustment	
Alternator and air conditioner compressor belt	7 (0.28)	4 - 5 (0.16 - 0.20)	3.5 - 4.5 (0.138 - 0.177)	294 (30, 66)	730 - 818 (74.5 - 83.5, 164 - 184)	838 - 926 (85.5 - 94.5, 188 - 208)
Power steering oil pump belt	12 (0.47)	9 - 10 (0.35 - 0.39)	8 - 9 (0.31 - 0.35)	196 (20, 44)	348 - 436 (35.5 - 44.5, 78 - 98)	470 - 559 (48 - 57, 106 - 126)
Applied pushing force	98N (10kg, 22lb)			—		
Radiator cap relief pressure		kPa (kg/cm <sup>2</sup> , psi)		78 - 98 (0.8 - 1.0, 11 - 14)		
Standard						
Limit				59 (0.6, 9)		
Cooling system leakage testing pressure	kPa (kg/cm <sup>2</sup> , psi)		157(1.6, 23)			
Compression pressure		kPa (kg/cm <sup>2</sup> , psi)/rpm		1,275 (13.0, 185) /300		
Standard						
Minimum				981 (10.0, 142)/300		
Spark plug	Standard type		PLFR5A - 11			
	Hot type		PLFR4A - 11			
	Cold type		PLFR6A - 11			

**ENGINE TUNE-UP DATA (VK45DE)**

Engine model	VK45DE	
Firing order	1-8-7-3-6-5-4-2	
Idle speed A/T (In "P" or "N" position)	rpm	650±50
Ignition timing (BTDC at idle speed)	12°±5°	
CO% at idle	0.7 - 9.9 % and engine runs smoothly	
Tensions of drive belts	Auto adjustment by auto tensioner	
Radiator cap relief pressure	78-98 (0.8-1.0 , 11-14 )	
Standard	kPa (kg/cm <sup>2</sup> , psi)	
Cooling system leakage testing pressure	157(1.6, 23)	
Standard	kPa (kg/cm <sup>2</sup> , psi)	
Compression pressure	1,320 (13.5, 191) /300	
Standard	kPa (kg/cm <sup>2</sup> , psi)/rpm	
Minimum	1,130 (11.5, 164)/300	
Spark plug	Standard type	PLFR5A - 11
	Hot type	PLFR4A - 11
	Cold type	PLFR6A - 11

**FRONT WHEEL ALIGNMENT (Unladen\* )**

ELS0003X

Camber	Degree minute (Decimal degree)	Minimum	- 1° 29' ( - 1.48° )
		Nominal	- 0° 44' ( - 0.73° )
		Maximum	0° 01' ( 0.02° )
		Left and right difference	45' ( 0.75° ) or less
Caster	Degree minute (Decimal degree)	Minimum	3° 02' ( 3.03° )
		Nominal	3° 47' ( 3.78° )
		Maximum	4° 32' ( 4.53° )
		Left and right difference	45' ( 0.75° ) or less
Kingpin inclination	Degree minute (Decimal degree)	Minimum	12° 20' ( 12.33° )
		Nominal	13° 05' ( 13.08° )
		Maximum	13° 50' ( 13.83° )
Total toe-in	Distance (A - B)	Minimum	0.6 mm ( 0.024 in )
		Nominal	1.6 mm ( 0.063 in )
		Maximum	2.6 mm ( 0.102 in )
	Angle (left plus right)	Minimum	-
		Nominal	6' ( 0.1° )
		Maximum	-
Wheel turning angle (Full turn)	Inside	Minimum	32° 00' ( 32.0° )
		Nominal	35° 00' ( 35.0° )
		Maximum	36° 00' ( 36.0° )
	Outside	Nominal	30° 00' ( 30.0° )

\* : Fuel, engine coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.

**REAR WHEEL ALIGNMENT (Unladen\*)**

ELS0003Y

Camber Degree minute (Decimal degree)		Minimum	- 1° 18' ( - 1.30° )
		Nominal	- 0° 48' ( - 0.80° )
		Maximum	- 0° 18' ( - 0.30° )
Total toe-in	Distance ( A - B )	Minimum	2.4 mm ( 0.094 in )
		Nominal	4.7 mm ( 0.185 in )
		Maximum	7.0 mm ( 0.276 in )
	Angle (left plus right ) Degree minute (Degree)	Minimum	0° 05' ( 0.08° )
		Nominal	0° 10' ( 0.17° )
		Maximum	0° 15' ( 0.25° )

\* : Fuel, engine coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.

**BRAKE**

ELS0003Z

Front brake	Pad wear limit	2.0 ( 0.079 )
	Rotor repair limit	26.0 mm ( 1.024 in )
Rear brake	Pad wear limit	2.0 mm ( 0.079 in )
	Rotor repair limit	14.0 mm ( 0.551 in )
Pedal free height		161.5 - 171.5 mm ( 6.358 - 6.752 in )
Pedal depressed height*		90 mm ( 3.54 in )

\* : Under force of 490 N( 50 kg, 110 lb ) with engine running.

**REFILL CAPACITIES**

ELS00040

UNIT		Liter	US measure
Fuel tank		90	23 - 3/4 gal
Coolant ( With reservoir tank )	VQ35DE	8.6	9 - 1/8 qt
	VK45DE	10.0	10 - 5/8 qt
Engine(VQ35DE)	Drain and refill		
	With oil filter change	4.7	5 qt
	Without oil filter change	4.4	4 - 5/8 qt
	Dry engine (Overhaul)	5.4	5 - 3/4 qt
Engine(VK45DE)	Drain and refill		
	With oil filter change	6.6	7qt
	Without oil filter change	6.0	6 - 3/8 qt
	Dry engine (Overhaul)	7.7	8 - 1/8 qt
Transmission	A/T	10.3	10 - 7/8 qt
Transfer		1.25	2 - 5/8 pt
Differential carrier	Front	0.65	1 - 3/8 pt
	Rear	1.4	3 pt
Power steering system		1.0	1 - 1/8 qt
Air conditioning system	Compressor oil	0.18	6.0 fl oz
	Refrigerant	0.55 kg	1.21 lb

**TEST VALUE AND TEST LIMIT (GST ONLY — NOT APPLICABLE TO CONSULT-II)**

The following is the information specified in Mode 6 of SAE J1979.

The test value is a parameter used to determine whether a system/circuit diagnostic test is "OK" or "NG" while being monitored by the ECM during self-diagnosis. The test limit is a reference value which is specified as the maximum or minimum value and is compared with the test value being monitored.

These data (test value and test limit) are specified by Test ID (TID) and Component ID (CID) and can be displayed on the GST screen.

SRT item	Self-diagnostic test item	DTC	Test value (GST display)		Test limit	Conversion
			TID	CID		
CATALYST	Three way catalyst function (Bank 1)	P0420	01H	01H	Max.	1/128
		P0420	02H	81H	Min.	1
	Three way catalyst function (Bank 2)	P0430	03H	02H	Max.	1/128
		P0430	04H	82H	Min.	1
EVAP SYSTEM	EVAP control system (Small leak)	P0442	05H	03H	Max.	1/128mm <sup>2</sup>
	EVAP control system purge flow monitoring	P0441	06H	83H	Min.	20mV
	EVAP control system (Very small leak)	P0456	07H	03H	Max.	1/128mm <sup>2</sup>
HO2S	Heated oxygen sensor 1 (Bank 1)	P0133	09H	04H	Max.	16ms
		P1143	0AH	84H	Min.	10mV
		P1144	0BH	04H	Max.	10mV
		P0132	0CH	04H	Max.	10mV
		P0134	0DH	04H	Max.	1s
	Heated oxygen sensor 1 (Bank 2)	P0153	11H	05H	Max.	16ms
		P1163	12H	85H	Min.	10mV
		P1164	13H	05H	Max.	10mV
		P0152	14H	05H	Max.	10mV
		P0154	15H	05H	Max.	1s
	Heated oxygen sensor 2 (Bank 1)	P0139	19H	86H	Min.	10mV/500ms
		P1147	1AH	86H	Min.	10mV
		P1146	1BH	06H	Max.	10mV
		P0138	1CH	06H	Max.	10mV
	Heated oxygen sensor 2 (Bank 2)	P0159	21H	87H	Min.	10mV/500ms
		P1167	22H	87H	Min.	10mV
P1166		23H	07H	Max.	10mV	
P0158		24H	07H	Max.	10mV	
HO2S HTR	Heated oxygen sensor 1 heater (Bank 1)	P0032	29H	08H	Max.	20mV
		P0031	2AH	88H	Min.	20mV
	Heated oxygen sensor 1 heater (Bank 2)	P0052	2BH	09H	Max.	20mV
		P0051	2CH	89H	Min.	20mV
	Heated oxygen sensor 2 heater (Bank 1)	P0038	2DH	0AH	Max.	20mV
		P0037	2EH	8AH	Min.	20mV
	Heated oxygen sensor 2 heater (Bank 2)	P0058	2FH	0BH	Max.	20mV
		P0057	30H	8BH	Min.	20mV