

SERVICE BULLETIN

APPLICABILITY 1990, 1991, 1992 LEGACY AND 1992 SVX **DATE** 07-01-93

SUBJECT: SERVICE MANUAL CORRECTIONS

Please photocopy the attached corrections as necessary.

Use the text below each correction to properly place it in the indicated service manual(s).

By immediately inserting the corrections, the proper information will be conveyed each time the manual(s) is/are used.

CAUTION

VEHICLE SERVICING PERFORMED BY UNTRAINED PERSONS COULD RESULT IN SERIOUS INJURY TO THOSE PERSONS OR TO OTHERS.
Subaru Service Bulletins are intended for use by professional technicians ONLY. They are written to inform those technicians of conditions that may occur in some vehicles, or to provide information that could assist in the proper servicing of the vehicle. Properly trained technicians have the equipment, tools, safety instructions, and know-how to do the job correctly and safely. If a condition is described, DO NOT assume that this Service Bulletin applies to your vehicle, or that your vehicle will have that condition. Impreza is a Trademark and Legacy, Justy, Loyale and Subaru SVX are Registered Trademarks.

• **SELECT MONITOR FUNCTION MODE**

Mode: F11	
Condition: Ignition switch ON (Engine OFF) N range	
Specified data: PLDTY F11	
15%	(Throttle is fully open)
100%	(Throttle is fully closed)

1990 Legacy 3-2, 149 [T4A5]

• **SELECT MONITOR FUNCTION MODE**

Mode: F11	
Condition: Ignition switch ON (Engine OFF) N range	
Specified data: PLDTY F11	
5%	(Throttle is fully open)
100%	(Throttle is fully closed)

1992 SVX 3-2, 179 [T5A5]

• **SELECT MONITOR FUNCTION MODE**

Mode: F11	
Condition: Ignition switch ON (Engine OFF) N range	
Specified data: PLDTY F11	
5% (TURBO) 15% (Non-TURBO)	(Throttle is fully open)
100%	(Throttle is fully closed)

1991 Legacy 3-2, 149 [T4A5]
1992 Legacy 3-2, 183 [T5A5]

K: MODE F11 — LINE PRESSURE DUTY (PLDTY) —

CONDITION

- Ignition ON (engine OFF)
- N range

SPECIFIED DATA:

Throttle fully closed: 100%
Throttle fully open: 15%

1990 Legacy 3-2, 177 [T5K0]

K: MODE F11 — LINE PRESSURE DUTY (PLDTY) —

CONDITION

- Ignition ON (engine OFF)
- N range

SPECIFIED DATA:

Throttle fully closed: 100%
Throttle fully open: 15% (Non-TURBO)
5% (TURBO)

1991 Legacy 3-2, 177 [T5K0]
1992 Legacy 3-2, 211 [T6K0]

K: MODE F11 — LINE PRESSURE DUTY (PLDTY) —

CONDITION

- Ignition ON (engine OFF)
- N range

SPECIFIED DATA:

Throttle fully closed: 100%
Throttle fully open: 5%

1992 SVX 3-2, 209 [T6K0]

NOTE:

Use the Select Monitor with the appropriate cartridge to determine the PLDTY%. Refer to **Trouble Shooting Chart with Select Monitor.**

1990 Legacy 3-2, 91 [W3EO]

1991 Legacy 3-2, 91 [W3EO]

1992 Legacy 3-2, 125 [W3DO]

Place this note on the bottom left of the indicated page under item 5

Range	RPM	PLDTY%	Pressure
P	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
R	600 - 800	100	585.65 - 688.00 (5.95 - 7.00, 85 - 100)
	Stall	5	1419.34-1584.70 (14.42-16.10, 206-230)
D	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	15	888.81 - 1026.81 (9.03 - 10.43, 129 - 149)
3 Manual Button OFF	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	15	888.81 - 1026.81 (9.03 - 10.43, 129 - 149)
3 Manual Button On	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	5	1143.74-1281.54 (11.62-13.02, 166-186)
2 Manual Button OFF	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	15	888.81 - 1026.81 (9.03 - 10.43, 129 - 149)
2 Manual Button On	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	5	1143.74-1281.54 (11.62-13.02, 166-186)
1	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	15	888.81 - 1026.81 (9.03 - 10.43, 129 - 149)

1990 Legacy 3-2, 91 [W3EO]

Unit=kPa (kg/cm², psi)

Range	RPM	PLDTY%	Pressure
P	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
R	600 - 800	100	585.65 - 689.00 (5.95 - 7.00, 85 - 100)
	Stall	5	1419.34-1584.70 (14.42-16.10,206-230)
D	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	15	888.81 - 1026.61 (9.03 - 10.43, 129 - 149)
	Stall Turbo	5	1143.74-1281.54 (11.62-13.02, 166-186)
3 Manual Button Off	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	15	888.81 - 1026.61 (9.03 - 10.43, 129 - 149)
	Stall Turbo	5	1143.74-1281.54 (11.62-13.02, 166-186)
3 Manual Button On	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	5	1143.74-1281.54 (11.62-13.02, 166-186)
2 Manual Button Off	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	15	888.81 - 1026.61 (9.03 - 10.43, 129 - 149)
	Stall Turbo	5	1143.74-1281.54 (11.62-13.02, 166-186)
2 Manual Button On	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	5	1143.74-1281.54 (11.62-13.02, 166-186)
1	600 - 800	100	440.96 - 564.98 (4.48 - 5.74, 64 - 82)
	Stall	15	888.81 - 1026.61 (9.03 - 10.43, 129 - 149)
	Stall Turbo	5	1143.74-1281.54 (11.62-13.02, 166-186)

1991 Legacy 3-2, 91 [W3EO]
1992 Legacy 3-2, 125 [W3DO]