

PISTON AND RING SPECIFICATIONS

All measurements are given in inches.

Year	Engine Displacement Liters (cc)	Engine ID/VIN	Piston Clearance	Ring Gap			Ring Side Clearance		
				Top Compression	Bottom Compression	Oil Control	Top Compression	Bottom Compression	Oil Control
1995	1.8 (1820)	1	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	1.8 (1820)	2	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.2 (2212)	3	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.2 (2212)	4	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	3.3 (3318)	3	0.0004-0.0024	0.0079-0.0200	0.0146-0.0390	0.0079-0.0590	0.0016-0.0059	0.0012-0.0059	NA
1996	1.8 (1820)	1	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	1.8 (1820)	2	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.2 (2212)	3	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.2 (2212)	4	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.5 (2457)	6	0.0004-0.0020	0.0079-0.0390	0.0146-0.0390	0.0079-0.0590	0.0016-0.0059	0.0012-0.0059	NA
	3.3 (3318)	3	0.0004-0.0024	0.0079-0.0200	0.0146-0.0390	0.0079-0.0590	0.0016-0.0059	0.0012-0.0059	NA
1997	1.8 (1820)	2	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.2 (2212)	4	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.5 (2457)	6	0.0004-0.0020	0.0079-0.0390	0.0146-0.0390	0.0079-0.0590	0.0016-0.0059	0.0012-0.0059	NA
	3.3 (3318)	3	0.0004-0.0024	0.0079-0.0200	0.0146-0.0390	0.0079-0.0590	0.0016-0.0059	0.0012-0.0059	NA
1998	2.2 (2212)	4	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.5 (2457)	6	0.0004-0.0020	0.0079-0.0390	0.0146-0.0390	0.0079-0.0590	0.0016-0.0059	0.0012-0.0059	NA
1999-00	2.2 (2212)	4	0.0004-0.0020	0.0079-0.0390	0.0079-0.0390	0.0079-0.0590	0.0016-0.0590	0.0012-0.0590	NA
	2.5 (2457)	6	0.0004-0.0020	0.0079-0.0390	0.0146-0.0390	0.0079-0.0590	0.0016-0.0059	0.0012-0.0059	NA