

Brought to you by Eris Studios
NOT FOR RESALE

1. Recommended Materials

A: RECOMMENDED MATERIALS

1. GENERAL

To insure the best performance, always use the specified oil, gasoline, adhesive, sealant, etc. or a substitute of equivalent quality.

2. FUEL



Always use gasoline of the same or higher octane value than specified in the owner's manual. Ignoring the specifications below will result in damage or poor performance of engine and fuel injection system. Use the specified gasoline to correct performance.

Unleaded gasoline

In order to reduce air pollution, use unleaded gasoline for the vehicle equipped with catalytic converter. Using leaded gasoline may damage the catalytic converter.

3. LUBRICANTS

Use either lubricants in the table below or equivalent. See the table below to choose the correct SAE viscosity.

Lubricant	Recommended materials	
	API standard	ILSAC standard
Engine oil	SM "Energy conserving"  RM-00049	GF-4  RM-00002
Manual Transmission Oil	GL-5	—
AT front differential gear oil	GL-5	—
Rear differential gear oil	GL-5	—

Recommended Materials

RECOMMENDED MATERIALS

SAE viscosity No. and applicable temperature								
Engine oil								
(°C)	-30	-20	-10	0	10	20	30	40
(°F)	-22	-4	14	32	50	68	86	104
10W-30 or 10W-40								
5W-30 Recommend								
RM-00059								
Manual transmission oil, front differential gear oil and rear differential gear oil								
(°F)	-30	-20	-10	0	10	20	30	40
(°C)	-22	-4	14	32	50	68	86	104
90								
85W								
80W								
75W-90								
RM-00058								

4. FLUID

Use the fluids specified in the table below. Do not mix two different kinds or makes of fluid.

Fluid	Recommended materials	Alternative	Remarks
Automatic transmission fluid	SUBARU ATF HP	IDEMITSU: ATF HP CASTROL: Transmax J PENNZOIL QUAKER-STATE: PENNZOIL ATF-J	—
Power steering fluid	SUBARU ATF HP	DEXRON III	—
Brake fluid	FMVSS No. 116 DOT3	FMVSS No. 116 DOT4	—
Clutch fluid	FMVSS No. 116 DOT3	FMVSS No. 116 DOT4	—

Recommended Materials

RECOMMENDED MATERIALS

5. COOLANT

Use the coolants specified in the table below to protect the engine.

Coolant	Recommended materials	Item number	Alternative
Coolant	SUBARU coolant	000016218	Phosphoric acid (non-amine) type
Water for dilution	Distilled water	—	Tap water (Soft water)
Cooling system protective agent	Cooling system conditioner	SOA345001	No

6. REFRIGERANT

Standard air conditioners on Subaru vehicles use HFC134a refrigerant. Do not mix it with other refrigerants. Also, do not use any compressor oil except for DH-PR.

Air conditioner	Recommended materials	Item number	Alternative
Refrigerant	HFC134a	—	None
Compressor oil	DH-PR	—	None

7. GREASE

Use grease and supplementary lubricants shown in the table below.

Grease	Application point	Recommended materials	Item number	Alternative
Supplementary lubricants	<ul style="list-style-type: none"> • Oxygen sensor • Bolts etc. 	Spray type lubricant	004301003	—
Grease	MT main shaft	NICHIMOLY N-130	—	—
	Clutch master cylinder push rod	SILICONE GREASE G-40M	004404003	—
	<ul style="list-style-type: none"> • Gear shift lever • Clutch activating cylinder • Clutch pedal • Brake pedal • Clutch bearing • Clutch release lever • Select lever • Steering shaft bearing 	KOPR-KOTE	003603001	—
	Select lever (lock plate unit)	Suncall GLO-224	002948040	—
	Steering gearbox	VALIANT GREASE M-2	003608001	ONE LUBER SG ONE LUBER MO
	Disc brake	NIGLUBE RX-2	K0779GA102	—
	Brake pad	Molykote AS-880N	K0777YA010	—
	Front axle PTJ	NKG302	28495AE010	—
	Rear axle EBJ	NTG2218-M	28395AG010	—
	Front axle BJ	NTG2218-M	28395AG030	—
	<ul style="list-style-type: none"> • Front axle DOJ (STI model) • Rear axle EDJ (STI model) 	NKG205	28495AG010	—
	Rear axle DOJ (except for STI model)	NKG205	28495AG000	—
	<ul style="list-style-type: none"> • Door latch • Door striker 	SILICONE GREASE G-30M	004404002	—

8. ADHESIVE

Use the adhesives shown in the table below, or equivalent.

Adhesive	Application point	Recommended materials	Item number	Alternative
Adhesive	Windshield, rear window glass, rear quarter glass, rear gate and body	Dow Automotive Adhesive: ESSEX U-400HV or equivalent Glass primer: U-401 and U-402 Painted surface primer: U-413	—	—
	Rearview mirror base	REPAIR KIT IN MR	65029FC000	—
	Soft vinyl	CEMEDINE 540	—	3M's EC-776, EC-847 or EC-1022 (Spray type)
	Momentary sealant	CEMEDINE 3000	—	ARMSTRONG's Eastman 910

9. SEAL MATERIAL

Use the seal material shown in the table below, or equivalent.

Seal material	Application point	Recommended materials	Item number	Alternative	
Seal material	<ul style="list-style-type: none"> • Cylinder block • Torque converter clutch case • Transmission case • Transmission oil pan (6MT model) • Oil pump • DOHC rocker cover 	THREE BOND 1215	004403007	DOW CORNING No. 7038	
	Transmission oil pan (AT model)	THREE BOND 1217B	K0877YA020	—	
	<ul style="list-style-type: none"> • Rear differential • Oil pressure switch 	THREE BOND 1324	004403042	—	
	<ul style="list-style-type: none"> • Rear differential • Service hole plug 	THREE BOND 1105	004403010	DOW CORNING No. 7038	
	Steering adjusting screw	THREE BOND 1141	004403006	—	
	Camshaft cap	Non-turbo model	THREE BOND 1280B	K0877YA018	—
		Turbo model	THREE BOND 1215	004403007	—
	<ul style="list-style-type: none"> • Front sealing cover • Rear sealing cover 	3M Butyl Rubber 8626	—	—	
	Engine oil pan	THREE BOND 1207C	004403012	—	
	<ul style="list-style-type: none"> • Separator cover • DOHC semicircular plug 	THREE BOND 1280B	K0877YA018	—	

Recommended Materials

RECOMMENDED MATERIALS

Brought to you by Eris Studios
NOT FOR RESALE