2. Schedule SA07682

A: MAINTENANCE SCHEDULE 1 SA07682G24

		MAINTENANCE INTERVAL																	
		[Number of months or km (miles), whichever occurs first]																	
	Months	3	7.5	15	22.5	30	37.5	45	52.5	60	67.5		82.5				112.5	120	Remarks
	× 1,000 km	4.8	12	24	36	48	60	72	81.4	96	108	120	132	144	156	168	180	192	
	× 1,000 miles	3	7.5		22.5	30	37.5	45	52.5	60	67.5	75	82.5	90	97.5	105	112.5	120	
1	Engine oil	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
2	Engine oil filter	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
3	Spark plugs					R				R				R				R	For 2.5 L
										R								R	For 3.0 L
4	Drive belt(s)					1				ı				ı		R			
5	Camshaft Drive belt			,		1				ı				Ì		R			For 2.5 L
																			Note (1)
6	Valve clearance															ı			
8	Fuel line					(I)				(1)				(I)		ļ		<u> </u>	Note (2)
9	Fuel filter					(R)				(R)	ļ			(R)				R	Note (2)
10	Air cleaner element					R				R				R				R	Note (3)
11	Cooling system					1				1				ı				1	
12	Coolant					R				R				R				R	
13	Clutch system			-		ı		-				1		ı		1		I	
14	Transmission oil					i				1				ı				l	
15	ATF					ı				1				ı				- 1	Note (4)
16	Front & rear differential oil					I				I				-				ı	
17	Brake line			١		ı		1		ı		1		1		1		1	
18	Brake fluid					R				R				R				R	
19	Disc brake pads & discs									1				-				I	
20	Brake linings and drums					I.				I				l				ı	
21	Parking brake			ı		1		ı		1		ı		Ī		П		ı	
22	Suspension			1		ı		ı		ı		ı		1	-	1		1	
23	Wheel bearing									(l)								(1)	
24	Axle boots & joints			1		ı		ı		1		ı		1				ı	
25	Tire rotation		1	1	1	1	-	1	1	1	1	ı	ı	ı	ı	ı	1	ı	Note (5)
26	Steering system (Power steering)			ı		I		1		I		j		1		Ι		I	
27	Supplement restraint system																		

Symbols used:

R: Replace

I: Inspection

(R) or (I): Recommended service for safe vehicle operation.

NOTE:

- (1) Periodic inspection and replacement of the camshaft drive chains on the 3.0 liter models are not required.
- (2) This inspection is not required to maintain emission warranty eligibility and it does not affect the manufacturer's obligations under EPA's in-use compliance program.
- (3) When the vehicle is used in extremely dusty conditions, the air cleaner element should be replaced more often.
- (4) ATF filter is maintenance free part. ATF filter needs replacement, when it has physically damaged or ATF leaked.
- (5) A tire should be replaced when the tread wear indicator appears as a solid band across the tread. The indicators appear when the remaining tread has been worn to 1.6 mm (0.063 in) or less.

B: MAINTENANCE SCHEDULE 2 SA07682G25

Item	Every	Repeat short distance drive	Repeat rough/muddy road drive	Extremely cold weather area	Salt or other corrosive used or coastal area	High humidity or mountain area	Repeat tow- ing trailer
Engine oil	3.75 months	R		R			R
	6,000 km						
	3,750 miles						
Engine oil filter	3.75 months	R		R			R
	6,000 km]					
	3,750 miles						
Fuel filter	15 months				I		
	24,000 km						
	15,000 miles						
Fuel line	15 months				l		
	24,000 km						
	15,000 miles						
Transmission oil	15 months						R
	24,000 km						
	15,000 miles						
ATF	15 months						R
	24,000 km						
	15,000 miles	1					
Front & rear differ-	15 months						R
ential oil	24,000 km]					
	15,000 miles]					
Brake line	15 months	1	1		1		l
	24,000 km]					
	15,000 miles						
Brake fluid	15 months				·	R	
	24,000 km		1	1			
	15,000 miles]					
Disc brake pads &	15 months	ı	I		I		1
discs	24,000 km						
	15,000 miles						
Brake linings and	15 months	l	l		ı		
drums	24,000 km						
	15,000 miles					·	
Parking brake	15 months	ı			1		I
	24,000 km						
	15,000 miles	1					
Suspension	7.5 months		1	1	I		ı
	12,000 km]					
	7,500 miles						
Axle boots &	7.5 months	I	1	I			l
joints	12,000 km						
	7,500 miles						
Steering system	7.5 months	ı	l	1			
(Power steering)	12,000 km						
	7,500 miles						