

# SPECIFICATIONS

# *SPC*

---

	<b>Page</b>
1. Legacy.....	2
2. OUTBACK.....	6
3. PICKUP.....	11



# LEGACY

## SPECIFICATIONS

### 1. Legacy

#### A: DIMENSIONS

Model			Sedan		Station Wagon	
					2.5 L	
					AWD	
					ALL	
Overall length			mm (in)	4,685 (184.4)	4,760 (187.4)	
Overall width			mm (in)	1,745 (68.7)	1,745 (68.7)	
Overall height			mm (in)	1,415 (55.7)	1,525 (60.0)*2	
Compartment	Leg room	Front Max.	mm (in)	1,101 (43.3)	1,101 (43.3)	
		Rear Min.	mm (in)	868 (34.2)	871 (34.3)	
	Head room	Front	mm (in)	987 (38.9), 967 (38.1)*1	1,020 (40.2), 977 (38.5)*1	
		Rear	mm (in)	930 (36.6)	994 (39.1), 945 (37.2)*1	
	Shoulder room	Front	mm (in)	1,368 (53.9)	1,368 (53.9)	
		Rear	mm (in)	1,362 (53.6)	1,362 (53.6)	
Wheelbase			mm (in)	2,650 (104.3)	2,650 (104.3)	
Tread		Front	mm (in)	1,460 (57.5)	1,460 (57.5)	
		Rear	mm (in)	1,460 (57.5)	1,455 (57.3)	
Minimum road clearance		M.L.V.W.	mm (in)	115 (4.5)	120 (4.7)	
		C.W.	mm (in)	155 (6.1)	160 (6.3)	

\*1: With sunroof

\*2: Including roof rail

#### B: ENGINE

Model		Sedan/Station Wagon	
Engine type		Horizontally opposed, liquid cooled, 4-cylinder, 4-stroke gasoline engine	
Valve arrangement		Overhead camshaft type	
Bore × Stroke	mm (in)	99.5 × 79.0 (3.917 × 3.110)	
Displacement	cm <sup>3</sup> (cu in)	2,457 (149.9)	
Compression ratio		10.0	
Firing order		1 — 3 — 2 — 4	
Idle speed at Park/Neutral position	rpm	650 (MT), 700 (AT)	
Maximum output	kW (HP)/rpm	123 (165)/5,600*1	119 (160)/5,600*2
Maximum torque	N·m (kgf-m, ft-lb)/rpm	226 (23.0, 166)/3,600	

\*1: Except U5

\*2: U5

#### C: ELECTRICAL

Model		Sedan/Station Wagon	
Ignition timing at idling speed		BTDC/rpm	
		10°±8°/650 (MT), 15°±8°/700 (AT)	
Spark plug	Type and manufacturer	CHAMPION: RC10YC4 (Standard)*1 NGK: BKR5E-11*1 NGK: BKR6E-11*1	NGK: FR5AP-11 (Standard)*2
Alternator		12V — 90A	
Battery	Reserve capacity	min	
	Cold cranking amperes	amp.	
		90 (MT), 110 (AT)	
		430 (MT), 490 (AT)	

\*1: Except U5

\*2: U5

**D: TRANSMISSION**

Model		Sedan/Station Wagon	
		AWD	
Transmission type		5MT	4AT
Clutch type		DSPD	TCC
Gear ratio	1st	3.454	2.785*1, 3.027*2
	2nd	2.062	1.545*1, 1.619*2
	3rd	1.448	1.000
	4th	1.088	0.694
	5th	0.780	—
	Reverse	3.333	2.272
Reduction gear (Front drive)	1st reduction	Type of gear	—
		Gear ratio	—
	Final reduction	Type of gear	Hypoid
		Gear ratio	4.111*2
Reduction gear (Rear drive)	Transfer reduction	Type of gear	Helical
		Gear ratio	1.000
	Final reduction	Type of gear	Hypoid
		Gear ratio	4.111*2

5MT: 5-forward speeds with synchromesh and 1-reverse – with center differential and viscous coupling  
 4AT: Electronically controlled fully-automatic, 4-forward speeds and 1-reverse – with hydraulically controlled transfer clutch  
 \*1: L, L-S  
 \*2: 2.5 GT, 2.5 GTLO  
 DSPD: Dry Single Plate Diaphragm  
 TCC: Torque Converter Clutch

**E: STEERING**

Type	Rack and Pinion	
Turns, lock to lock	3.2	
Minimum turning circle	m (ft)	Curb to curb: 11.6 (38.1), Wall to wall: 10.8 (35.4)

**F: SUSPENSION**

Front	Macpherson strut type, Independent, Coil spring
Rear	Multi-link type, Independent, Coil spring

**G: BRAKE**

Model	With ABS
Service brake system	Dual circuit hydraulic with vacuum suspended power unit
Front	Ventilated disc brake
Rear	Disc brake
Parking brake	Mechanical on rear brakes

**H: TIRE**

Model	15-inch wheel	16-inch wheel
Size	P205/60R15 90H	P205/55R16 89H
Type	Steel belted radial, Tubeless	

# LEGACY

## SPECIFICATIONS

### I: CAPACITY

Model		AWD	
		5MT	4AT
Fuel tank	ℓ (US gal, Imp gal)	64 (16.9, 14.1)	
Engine oil (Replacement)	ℓ (US qt, Imp qt)	Approx. 4.0 (4.2, 3.5)	
Transmission gear oil	ℓ (US qt, Imp qt)	3.5 (3.7, 3.1)	—
Automatic transmission fluid	ℓ (US qt, Imp qt)	—	9.3 – 9.6 (9.8 – 10.1, 8.2 – 8.4)
AT differential gear oil	ℓ (US qt, Imp qt)	—	1.1 – 1.3 (1.2 – 1.4, 1.0 – 1.1)
AWD rear differential gear oil	ℓ (US qt, Imp qt)	0.8 (0.8, 0.7), 0.9 (0.9, 0.8)*	
Power steering fluid	ℓ (US qt, Imp qt)	0.7 (0.7, 0.6)	
Engine coolant	ℓ (US qt, Imp qt)	6.8 (7.2, 6.0)	6.7 (7.1, 5.9)

\*: L

### J: WEIGHT

#### 1. U.S. SPEC. VEHICLE

Model			Sedan			
			2.5 L			
			AWD			
			L		2.5 GT	
			5MT	4AT	5MT	4AT-SS
Curb weight (C.W.)	Front	kg (lb)	823 (1,815)	848 (1,870)	857 (1,890)	880 (1,940)
	Rear	kg (lb)	660 (1,455)	662 (1,460)	683 (1,505)	685 (1,510)
	Total	kg (lb)	1,483 (3,270)	1,510 (3,330)	1,540 (3,395)	1,565 (3,450)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,007 (2,220)			
	Rear	kg (lb)	989 (2,180)			
	Total	kg (lb)	1,996 (4,400)			

Model			Station Wagon			
			2.5 L			
			AWD			
			L		2.5 GT	
			5MT	4AT	5MT	4AT-SS
Curb weight (C.W.)	Front	kg (lb)	823 (1,815)	855 (1,885)	857 (1,890)	882 (1,945)
	Rear	kg (lb)	701 (1,545)	701 (1,545)	730 (1,610)	735 (1,620)
	Total	kg (lb)	1,524 (3,360)	1,556 (3,430)	1,588 (3,500)	1,617 (3,565)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,002 (2,210)			
	Rear	kg (lb)	1,064 (2,345)			
	Total	kg (lb)	2,066 (4,555)			

**2. CANADA SPEC. VEHICLE**

Model		Sedan			
		2.5 L			
		AWD			
		L	2.5 GT		
		4AT	5MT	4AT-SS	
Curb weight (C.W.)	Front	kg (lb)	839 (1,850)	844 (1,860)	866 (1,910)
	Rear	kg (lb)	662 (1,460)	683 (1,505)	685 (1,510)
	Total	kg (lb)	1,501 (3,310)	1,527 (3,365)	1,551 (3,420)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,007 (2,220)		
	Rear	kg (lb)	989 (2,180)		
	Total	kg (lb)	1,996 (4,400)		

Model		Sedan		
		2.5 L		
		AWD		
		2.5 GTLO		
		5MT	4AT-SS	
Curb weight (C.W.)	Front	kg (lb)	839 (1,850)	862 (1,900)
	Rear	kg (lb)	678 (1,495)	680 (1,500)
	Total	kg (lb)	1,517 (3,345)	1,542 (3,400)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,007 (2,220)	
	Rear	kg (lb)	989 (2,180)	
	Total	kg (lb)	1,996 (4,400)	

Model		Station Wagon			
		2.5 L			
		AWD			
		L	2.5 GT		
		5MT	4AT	4AT-SS	
Curb weight (C.W.)	Front	kg (lb)	812 (1,790)	841 (1,855)	869 (1,915)
	Rear	kg (lb)	701 (1,545)	701 (1,545)	735 (1,620)
	Total	kg (lb)	1,513 (3,335)	1,542 (3,400)	1,604 (3,535)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,002 (2,210)		
	Rear	kg (lb)	1,064 (2,345)		
	Total	kg (lb)	2,066 (4,555)		

**3. TIWAN SPEC. VEHICLE**

Model		Sedan		Station Wagon		
		2.5 L				
		AWD				
		L	2.5 GT	L	L-S	
		4AT	4AT-SS	4AT		
Curb weight (C.W.)	Front	kg (lb)	835 (1,840)	866 (1,910)	841 (1,855)	851 (1,875)
	Rear	kg (lb)	662 (1,460)	685 (1,510)	701 (1,545)	719 (1,585)
	Total	kg (lb)	1,497 (3,300)	1,551 (3,420)	1,542 (3,400)	662 (3,460)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,007 (2,220)		1,002 (2,210)	
	Rear	kg (lb)	989 (2,180)		1,064 (2,345)	
	Total	kg (lb)	1,996 (4,400)		2,066 (4,555)	

# OUTBACK

## SPECIFICATIONS

## 2. OUTBACK

### A: DIMENSIONS

Model				Sedan		Wagon	
				AWD		AWD	
				2.5 L	3.0 L	2.5 L	3.0 L
Overall length	mm (in)	4,685 (184.4)		4,760 (187.4)			
Overall width	mm (in)	1,745 (68.7)		1,745 (68.7)			
Overall height	mm (in)	1,480 (58.3)		1,580 (62.2)			
Compartment	Leg room	Front Max.	mm (in)	1,101 (43.3)		1,101 (43.3)	
		Rear Min.	mm (in)	868 (34.2)		871 (34.3)	
	Head room	Front	mm (in)	987 (38.9), 967 (38.1)*1		1,020 (40.2), 977 (38.5)*1	
		Rear	mm (in)	930 (36.6)		994 (39.1), 945 (37.2)*1	
	Shoulder room	Front	mm (in)	1,368 (53.9)		1,368 (53.9)	
		Rear	mm (in)	1,362 (53.6)		1,362 (53.6)	
Wheelbase	mm (in)	2,650 (104.3)		2,650 (104.3)			
Tread	Front	mm (in)	1,470 (57.9)		1,470 (57.9)		
	Rear	mm (in)	1,465 (57.7)		1,465 (57.7)		
Minimum road clearance	M.L.V.W.	mm (in)	144 (5.7)	142 (5.6)	144 (5.7)	137 (5.4)	
	C.W.	mm (in)	185 (7.3)	200 (7.8)	185 (7.3)	200 (7.9)	

\*1: With sunroof

### B: ENGINE

Model		Sedan/Wagon	
		2.5 L	3.0 L
Engine type		Horizontally opposed, liquid cooled, 4-cylinder, 4-stroke gasoline engine	Horizontally opposed, liquid cooled, 6-cylinder, 4-stroke gasoline engine
Valve arrangement		Overhead camshaft type	Double overhead camshaft type
Bore × Stroke	mm (in)	99.5 × 79.0 (3.917 × 3.110)	89.2 × 80.0 (3.512 × 3.150)
Displacement	cm <sup>3</sup> (cu in)	2,457 (149.9)	3,000 (183.06)
Compression ratio		10.0	10.7
Firing order		1 — 3 — 2 — 4	1 — 6 — 3 — 2 — 5 — 4
Idle speed at Park/ Neutral position	rpm	650 (MT), 700 (AT)	
Maximum output	kW (HP)/rpm	123 (165)/5,600*1 119 (160)/5,600*2	
Maximum torque	N·m (kgf·m, ft·lb)/rpm	226 (23.0, 166)/3,600	
		282 (28.8, 208)/4,400	

\*1: Except U5

\*2: U5

**C: ELECTRICAL**

Model		Sedan/Wagon	
		2.5 L	3.0 L
Ignition timing at idling speed	BTDC/rpm	10°±8°/650 (MT), 15°±8°/700 (AT)	
Spark plug	Type and manufacturer	CHAMPION: RC10YC4 (Standard)*1 NGK: BKR5E-11*1 NGK: BKR6E-11*1 NGK: FR5AP-11 (Standard)*2	NGK: PLFR6A-11
Alternator		12V — 90A	12V — 100A
Battery	Reserve capacity	min	90 (MT), 110 (AT)
	Cold cranking amperes	amp.	430 (MT), 490 (AT)

\*1: Except U5

\*2: U5

**D: TRANSMISSION**

Model		Sedan/Wagon		
		2.5 L		3.0 L
		AWD		
Transmission type		5MT	4AT	
Clutch type		DSPD	TCC	
Gear ratio	1st	3.454	3.027	2.785
	2nd	2.062	1.619	1.545
	3rd	1.448	1.000	
	4th	1.088	0.694	
	5th	0.871	—	
	Reverse	3.333	2.272	
Reduction gear (Front drive)	1st reduction	Type of gear	—	
		Gear ratio	—	
	Final reduction	Type of gear	Hypoid	
		Gear ratio	4.111	4.444
Reduction gear (Rear drive)	Transfer reduction	Type of gear	Helical	
		Gear ratio	1.000	
	Final reduction	Type of gear	Hypoid	
		Gear ratio	4.111	4.444

5MT: 5-forward speed with synchromesh and 1-reverse – with center differential and viscous coupling

4AT: Electronically controlled fully-automatic, 4-forward speeds and 1-reverse – with hydraulically controlled transfer clutch

DSPD: Dry Single Plate Diaphragm

TCC: Torque Converter Clutch

**E: STEERING**

Type	Rack and Pinion	
Turns, lock to lock	3.4	
Minimum turning circle	m (ft)	Curb to curb: 12.0 (39.4), Wall to wall: 11.2 (36.7)

**F: SUSPENSION**

Front	Macpherson strut type, Independent, Coil spring	
Rear	Multi-link type, Independent, Coil spring	

# OUTBACK

## SPECIFICATIONS

### G: BRAKE

Model	With ABS
Service brake system	Dual circuit hydraulic with vacuum suspended power unit
Front	Ventilated disc brake
Rear	Disc brakes
Parking brake	Mechanical on rear brakes

### H: TIRE

Model	16-inch wheel	
Size	P215/60R16*	P225/60R16 97H
Type	Steel belted radial, Tubeless	

\*: Recommended winter (snow) tire size.

### I: CAPACITY

Model		2.5 L		3.0 L	
		AWD			
		5MT	4AT		
Fuel tank	ℓ (US gal, Imp gal)	64 (16.9, 14.1)			
Engine oil (Replacement)	ℓ (US qt, Imp qt)	Approx. 4.0 (4.2, 3.5)		Approx. 5.6 (5.9, 4.9)	
Transmission gear oil	ℓ (US qt, Imp qt)	3.5 (3.7, 3.1)	—		
Automatic transmission fluid	ℓ (US qt, Imp qt)	—	9.3 – 9.6 (9.8 – 10.1, 8.2 – 8.4)		
AT differential gear oil	ℓ (US qt, Imp qt)	—	1.1 – 1.3 (1.2 – 1.4, 1.0 – 1.1)		
AWD rear differential gear oil	ℓ (US qt, Imp qt)	0.8 (0.8, 0.7)			
Power steering fluid	ℓ (US qt, Imp qt)	0.7 (0.7, 0.6)			
Engine coolant	ℓ (US qt, Imp qt)	6.8 (7.2, 6.0)	6.7 (7.1, 5.9)	7.9 (8.4, 7.0)	

### J: WEIGHT

#### 1. U.S. SPEC. VEHICLE

Model		Sedan			
		2.5 L		3.0 L	
		AWD			
		4AT		4AT*1	
Curb weight (C.W.)	Front	kg (lb)	907 (2,000)	943 (2,080)	
	Rear	kg (lb)	692 (1,525)	694 (1,530)	
	Total	kg (lb)	1,599 (3,525)	1,637 (3,610)	
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,007 (2,220)	1,061 (2,340)	
	Rear	kg (lb)	989 (2,180)	989 (2,180)	
	Total	kg (lb)	1,996 (4,400)	2,050 (4,520)	

Model		Wagon				
		2.5 L				
		Cold weather		LTD		
		5MT	4AT	5MT	4AT	
Curb weight (C.W.)	Front	kg (lb)	857 (1,890)	882 (1,945)	871 (1,920)	896 (1,975)
	Rear	kg (lb)	712 (1,570)	717 (1,580)	735 (1,620)	739 (1,630)
	Total	kg (lb)	1,569 (3,460)	1,599 (3,525)	1,606 (3,540)	1,635 (3,605)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,002 (2,210)			
	Rear	kg (lb)	1,064 (2,345)			
	Total	kg (lb)	2,066 (4,555)			



# OUTBACK

## SPECIFICATIONS

Model		Wagon				
		2.5 L		3.0 L		
		OTHERS		EXCEPT S	S	
		5MT	4AT	4AT*1		
Curb weight (C.W.)	Front	kg (lb)	855 (1,885)	880 (1,940)	943 (2,080)	934 (2,060)
	Rear	kg (lb)	712 (1,570)	716 (1,580)	741 (1,635)	723 (1,595)
	Total	kg (lb)	1,563 (3,445)	1,597 (3,520)	1,684 (3,715)	1,658 (3,655)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,002 (2,210)		1,061 (2,340)	
	Rear	kg (lb)	1,064 (2,345)		1,070 (2,360)	
	Total	kg (lb)	2,066 (4,555)		2,131 (4,700)	

\*1: Excludes the weights of audio, VDC

## 2. CANADA SPEC. VEHICLE

Model		Sedan				
		2.5 L		3.0 L		
		AWD				
		4AT		4AT*1		
Curb weight (C.W.)	Front	kg (lb)	894 (1,970)		943 (2,080)	
	Rear	kg (lb)	692 (1,525)		694 (1,530)	
	Total	kg (lb)	1,586 (3,495)		1,637 (3,610)	
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,007 (2,220)		1,061 (2,340)	
	Rear	kg (lb)	989 (2,180)		989 (2,180)	
	Total	kg (lb)	1,996 (4,400)		2,050 (4,520)	

Model		Wagon					
		2.5 L		3.0 L			
		Cold Weather		LTD	EXCEPT S	S	
		5MT	4AT	4AT*1			
Curb weight (C.W.)	Front	kg (lb)	844 (1,860)	869 (1,915)	882 (1,945)	943 (2,080)	934 (2,060)
	Rear	kg (lb)	712 (1,570)	717 (1,580)	739 (1,630)	741 (1,635)	723 (1,595)
	Total	kg (lb)	1,556 (3,430)	1,586 (3,495)	1,621 (3,575)	1,684 (3,715)	1,658 (3,655)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,002 (2,210)		1,061 (2,340)		
	Rear	kg (lb)	1,064 (2,345)		1,070 (2,360)		
	Total	kg (lb)	2,066 (4,555)		2,131 (4,700)		

\*1: Excludes the weights of audio, VDC

## 3. TAIWAN SPEC. VEHICLE

Model		Wagon				
		2.5 L				
		AWD				
		4AT				
Curb weight (C.W.)	Front	kg (lb)	882 (1,945)			
	Rear	kg (lb)	739 (1,630)			
	Total	kg (lb)	1,621 (3,575)			
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,002 (2,210)			
	Rear	kg (lb)	1,064 (2,345)			
	Total	kg (lb)	2,066 (4,555)			

# OUTBACK

## SPECIFICATIONS

---

### 4. CHILE SPEC. VEHICLE

Model		Sedan		Wagon	
		3.0 L			
		AWD			
		4AT			
Curb weight (C.W.)	Front	kg (lb)	950 (2,095)	950 (2,095)	950 (2,095)
	Rear	kg (lb)	694 (1,530)	741 (1,635)	741 (1,635)
	Total	kg (lb)	1,644 (3,625)	1,691 (3,730)	1,691 (3,730)
Gross vehicle weight (G.V.W.)	Front	kg (lb)	1,061 (2,340)	1,061 (2,340)	1,061 (2,340)
	Rear	kg (lb)	989 (2,180)	1,070 (2,360)	1,070 (2,360)
	Total	kg (lb)	2,050 (4,520)	2,131 (4,700)	2,131 (4,700)

### 3. PICKUP

#### A: DIMENSIONS

Model				AWD	
				Non-turbo model	Turbo model
Overall length		mm (in)	4,910 (193.3)		
Overall width		mm (in)	1,780 (70.1)		
Overall height		mm (in)	1,577 (62.1)	1,590 (62.6)	
Compartment	Leg room	Front Max.	mm (in)	1,101 (43.3)	
		Rear Min.	mm (in)	851 (33.50)	
	Head room	Front	mm (in)	973 (38.31)	
		Rear	mm (in)	947 (37.28)	
	Shoulder room	Front	mm (in)	1,368 (53.9)	
		Rear	mm (in)	1,362 (53.6)	
Wheelbase		mm (in)	2,650 (104.3)		
Tread	Front	mm (in)	1,470 (57.9)		
	Rear	mm (in)	1,465 (57.7)		
Minimum road clearance	M.L.V.W.	mm (in)	173 (6.81)	163 (6.42)	
	C.W.	mm (in)	213 (8.39)		

#### B: ENGINE

Model		2.5 L	Turbo 2.5 L
Engine type		Horizontally opposed, liquid cooled, 4-cylinder, 4-stroke gasoline engine	
Valve arrangement		Overhead camshaft type	DOHC
Bore × Stroke		mm (in) 99.5 × 79.0 (3.917 × 3.110)	
Displacement		cm <sup>3</sup> (cu in) 2,457 (149.9)	
Compression ratio		10.0	8.2±0.2
Firing order		1 — 3 — 2 — 4	
Idle speed at Park/Neutral position		rpm MT:650 AT:700	rpm AT:700±100 MT:700±100
Maximum output		kW (HP)/rpm 123 (165)/5,600	
Maximum torque		N·m (kgf-m, ft-lb)/rpm 226 (23.0, 166)/3,600	

#### C: ELECTRICAL

Model		2.5 L	Turbo 2.5 L
Ignition timing at idling speed		BTDC/rpm MT:10°±8°/650, AT:15°±8°/700	MT: 13°±10°/700 AT: 17°±10°/700
Spark plug	Type and manufacturer	CHAMPION: RC10YC4 (Standard) NGK: BKR5E-11 NGK: BKR6E-11	NGK: ILFR6B
Alternator		12V — 90A	
Battery	Reserve capacity	min 90 (MT), 110 (AT)	
	Cold cranking amperes	amp. 430 (MT), 490 (AT)	

# PICKUP

## SPECIFICATIONS

### D: TRANSMISSION

Model		2.5 L Non-turbo		2.5 L Turbo		
Transmission type		5MT	4AT	5MT	4AT	
Clutch type		DSPD	TCC	DSPD	TCC	
Gear ratio	1st	3.454	3.027	3.454	2.785	
	2nd	2.062	1.619	1.947	1.545	
	3rd	1.448	1.000	1.366	1.000	
	4th	1.088	0.694	0.972	0.694	
	5th	0.871	—	0.738	—	
	Reverse	3.333	2.272	3.333	2.272	
Reduction gear (Front drive)	1st reduction	Type of gear	—	Helical	—	Helical
		Gear ratio	—	1.000	—	1.000
	Final reduction	Type of gear	Hypoid		Hypoid	
		Gear ratio	4.111	4.444	4.444	4.444
Reduction gear (Rear drive)	Transfer reduction	Type of gear	Helical	—	Helical	—
		Gear ratio	1.000	—	1.000	—
	Final reduction	Type of gear	Hypoid		Hypoid	
		Gear ratio	4.111	4.444	4.444	4.444

5MT: 5-forward speed with synchromesh and 1-reverse – with center differential and viscous coupling

4AT: Electronically controlled fully-automatic, 4-forward speeds and 1-reverse – with hydraulically controlled transfer clutch

DSPD: Dry Single Plate Diaphragm

TCC: Torque Converter Clutch

### E: STEERING

Type	Rack and Pinion	
Turns, lock to lock	3.4	
Minimum turning circle	m (ft)	Curb to curb: 12.0 (39.4), Wall to wall: 11.2 (36.7)

### F: SUSPENSION

Front	Macpherson strut type, Independent, Coil spring
Rear	Multi-link type, Independent, Coil spring

### G: BRAKE

Model	With ABS
Service brake system	Dual circuit hydraulic with vacuum suspended power unit
Front	Ventilated disc brake
Rear	Disc brakes
Parking brake	Mechanical on rear brakes

### H: TIRE

Model	16-inch wheel	
Size	P215/60R16*	P225/60R16 97H
Type	Steel belted radial, Tubeless	

\*: Recommended winter (snow) tire size.

**I: CAPACITY**

Model		AWD		AWD Turbo	
		5MT	4AT	5MT	4AT
Fuel tank	ℓ (US gal, Imp gal)	64 (16.9, 14.1)			
Engine oil (Replacement)	ℓ (US qt, Imp qt)	Approx. 4.0 (4.2, 3.5)			
Transmission gear oil	ℓ (US qt, Imp qt)	3.5 (3.7, 3.1)	—	3.5 (3.7, 3.1)	—
Automatic transmission fluid	ℓ (US qt, Imp qt)	—	9.3 – 9.6 (9.8 – 10.1, 8.2 – 8.4)	—	9.3 – 9.6 (9.8 – 10.1, 8.2 – 8.4)
AT differential gear oil	ℓ (US qt, Imp qt)	—	1.1 – 1.3 (1.2 – 1.4, 1.0 – 1.1)	—	1.1 – 1.3 (1.2 – 1.4, 1.0 – 1.1)
AWD rear differential gear oil	ℓ (US qt, Imp qt)	0.8 (0.8, 0.7)			
Power steering fluid	ℓ (US qt, Imp qt)	0.7 (0.7, 0.6)			
Engine coolant	ℓ (US qt, Imp qt)	6.8 (7.2, 6.0)	6.7 (7.1, 5.9)	7.7 (8.1, 6.8)	7.6 (8.0, 6.7)

**J: WEIGHT**

**1. U.S. SPEC. VEHICLE**

Model		AWD		AWD-S		AWD-B		
		5MT	4AT	5MT	4AT	5MT Non-Turbo	5MT Turbo	4AT Turbo
Curb weight (C.W.)	Front kg (lb)	844 (1,860)	873 (1,925)	839 (1,850)	869 (1,915)	889 (1,960)	894 (1,970)	914 (2,015)
	Rear kg (lb)	744 (1,640)	744 (1,640)	739 (1,630)	739 (1,630)	748 (1,650)	755 (1,665)	748 (1,650)
	Total kg (lb)	1,588 (3,500)	1,617 (3,565)	1,579 (3,480)	1,608 (3,545)	1,637 (3,610)	1,649 (3,635)	1,662 (3,665)
Gross vehicle weight (G.V.W.)	Front kg (lb)	1,002 (2,210)						
	Rear kg (lb)	1,063 (2,345)						
	Total kg (lb)	2,066 (4,555)						

**2. CANADA SPEC. VEHICLE**

Model		AWD		AWD-S		AWD-B		
		5MT	4AT	5MT	4AT	5MT Non-Turbo	5MT Turbo	4AT Turbo
Curb weight (C.W.)	Front kg (lb)	844 (1,860)	873 (1,925)	839 (1,850)	869 (1,915)	889 (1,960)	894 (1,970)	914 (2,015)
	Rear kg (lb)	744 (1,640)	744 (1,640)	739 (1,630)	739 (1,630)	748 (1,650)	755 (1,665)	748 (1,650)
	Total kg (lb)	1,588 (3,500)	1,617 (3,565)	1,579 (3,480)	1,608 (3,545)	1,637 (3,610)	1,649 (3,635)	1,662 (3,665)
Gross vehicle weight (G.V.W.)	Front kg (lb)	1,002 (2,210)						
	Rear kg (lb)	1,063 (2,345)						
	Total kg (lb)	2,066 (4,555)						

# PICKUP

SPECIFICATIONS

---

**MEMO:**