


## DISASSEMBLY


1. REMOVE NO. 3 SLIDING ROOF HOUSING SIDE MOUNTING BRACKETS
2. REMOVE SLIDING ROOF HOUSING REAR MOUNTING BRACKETS



### 3. REMOVE SLIDING ROOF SUNSHADE STOPPER


- (a) Remove the screw and stopper.
- (b) Perform the same procedure on the other side.

### 4. REMOVE SUNSHADE TRIM




### 5. REMOVE REAR ROOF DRIP CHANNEL

Remove the 2 screws and rear roof drip channel as shown in the illustration.




### 6. REMOVE REAR FRAME

Remove the 4 screws and rear frame.




### 7. REMOVE DRIVE CABLE

- (a) Remove the screw and sliding roof panel stopper.
- (b) Slide the drive cable rearward, then remove it.
- (c) Perform the same procedure on the other side.


**HINT:**

At the time of reassembly, please refer to the following items.


- Adjust the drive cable to a closed and tilted down position.
- Slide the cable forward or backward to align the 2 marks as shown in the illustration.
- Slide the cable to the forefront with your hand.

**8. REMOVE ROOF WIND DEFLECTOR PANEL****9. REMOVE GUIDE BLOCK**

- Remove the 2 screws and guide block.
- Perform the same procedure on the other side.

**10. REMOVE SLIDING ROOF HOUSING**

Remove the 6 screws and sliding roof housing.

**11. REMOVE CABLE GUIDE CASING**

Remove the 2 screws and cable guide casing.