

Mobil Delvac MX ESP 15W-40

Product Description

Mobil Delvac MX ESP 15W-40 is an extra high performance diesel engine oil that helps extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation (EGR) and Aftertreatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). Fully backwards compatible, Mobil Delvac MX ESP 15W-40 will also deliver the same exceptional performance in older conventional engines. As a result, it exceeds the API CJ-4, CI-4 PLUS and CH-4 service categories as well as key Original Equipment Manufacturer (OEM) requirements.

Mobil Delvac MX ESP 15W-40 is the result of extensive cooperative development work with major OEMs and is recommended for use in a wide range of heavy duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries. This product provides outstanding protection in the most demanding diesel engines of Caterpillar, Cummins, Detroit Diesel, Mack, Mercedes Benz, Navistar, Volvo, and others. Mobil Delvac MX ESP 15W-40 also meets the API SM specification for gasoline engines and mixed fleets.

Features and Benefits

Mobil Delvac MX ESP 15W-40 is formulated with Trimer additive technology and a mixed detergent system to deliver cutting-edge performance in both new and older engines. In addition to assuring excellent control of oil thickening due to soot build-up and outstanding TBN retention for long drain intervals, Mobil Delvac ESP 15W-40's advanced technology also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

The key benefits include:

Features	Advantages and Potential Benefits
Superior soot-viscosity control	Greater engine efficiency, long engine life and long oil life
Outstanding thermal and oxidative stability	Reduced low temperature sludge build-up and high temperature deposits
Excellent oil consumption control	Lower oil costs due to less make-up oil during operation
Excellent TBN reserves	Improved corrosion protection and extended drain intervals
Stay-in-grade shear stability	Maintains viscosity in severe, high temperature service for greater wear protection and long engine life
Excellent low temperature pumpability	Faster oil flow and reduced wear during engine start-up in low temperatures
Superb resistance to corrosive and abrasive wear	Long life of critical wear surfaces
Component compatibility	Long gasket, seal, and after treatment (DPF and DOC) life
Meets demanding specifications of key OEMs and latest API gasoline service category	One engine oil for mixed fleet operations



Applications

- Specifically recommended for the latest low-emissions, high performance diesel applications equipped with aftertreatment systems using Diesel Particulate Filter (DPF) and Diesel Oxidation Catalyst (DOC) technologies.
- Recommended for high-performance diesel applications including turbocharged designs featuring EGR Technology and diesel applications using older, naturally aspirated conventional designs.
- On-highway heavy-duty trucking and off-highway including: construction, mining, quarrying, and agriculture.
- On-highway applications operating in both high speed/high load and short haul pick-up/delivery.
- Off-highway applications operating in severe low speed/heavy load conditions
- Recommended for use in high performance gasoline engines and mixed fleet operations.
- Diesel-powered equipment from American and European OEMs

Specifications and Approvals

Mobil Delvac MX ESP 15W-40 Meets or Exceeds the following industry and builder specifications:

API CJ-4, CI-4 PLUS, CI-4, CH-4, CF-2, CF, SM, SL	X
ACEA E7, E9	X
Caterpillar ECF-3	X
JASO DH-2	X

Mobil Delvac MX ESP 15W-40 has the following builder approvals:

Cummins CES 20081	X
Detroit Diesel Power Guard Oil Specification 93K218 / 93K214	X
Mack EO-N Premium Plus 03 / Mack EO-O Premium Plus	X
MAN M3275	X
Deutz DQC II-05	X
Mercedes Benz MB-Approval 228.3, 228.31	X
Volvo VDS-4/ VDS-3 / VDS-2	X
Renault VI RLD-3	X

Mobil Delvac MX ESP 15W-40 is recommended for use in applications requiring:

API CG-4, CF-4	X
----------------	---

Typical Properties

Mobil Delvac MX ESP 15W-40

SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	114

Mobil Delvac MX ESP 15W-40

cSt @ 100°C	15.0
CCS, cP, ASTM D 5293	6500 @ -20°C
MRV, cP, ASTM D 4684	19,000 @ -25°C
HTHS @ 150°C, cP, ASTM D4683	4.3
Viscosity Index, ASTM D 2270	137
Sulfated Ash, wt%, ASTM D 874	0.98
Total Base #, mg KOH/g, ASTM D 2896	10.4
Pour Point, °C, ASTM D 97	-30
Flash Point, °C, ASTM D 92	236
Density @ 15°C kg/l, ASTM D 4052	0.876

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.
© 2007 Exxon Mobil Corporation. All rights reserved.