

Mobil Outboard Plus

Superior Performance Two-Stroke Outboard Engine Oil

Product Description

Mobil Outboard Plus is an superior performance, two-stroke engine oil that exceeds the latest manufacturer's requirements for modern, high performance, water-cooled two-stroke engines used in outboard marine applications. Mobil Outboard Plus offers clean engine and environmental performance. Mobil Outboard Plus is pre-diluted to facilitate mixing when added to fuel.

Features and Benefits

Mobil Outboard Plus is formulated from high purified conventional mineral oils and an ashless dispersant additive system providing outstanding protection against exhaust port deposits, corrosion and wear. Spark plug fouling and pre-ignition are also minimised promoting flawless operation. The product is ideal for use in both modern and older two stroke engine models. Key features and benefits include:

Features	Advantages and Potential Benefits
Good thermal and oxidation stability and deposit control	Cleaner engines resulting in reduced ring sticking and cylinder scuffing, extended engine life and more reliable operation
Outstanding anti-wear protection	Extended life of critical components and engine
Excellent corrosion protection properties	Longer engine life
Promotes cleaner combustion and reduced deposits in combustion area	Reduces plug fouling and exhaust port deposits thus minimising pre-ignition, extending spark plug and valve life and increasing fuel efficiency
Good high and low temperature capability	Wide range of ambient temperature application
Non-toxic to marine life	No lingering side affects to marine life

Applications

- Mobil Outboard Plus is recommended for use in all modern high-performance, water-cooled, two-stroke, as well as, smaller or older outboard engines. It is suitable for the two-stroke engines manufactured by Johnson, Mercury, OMC, Evinrude, Mariner, Force, Mercruiser, Yamaha, Suzuki, Nissan and Tohatsu or where NMMA TC-W, TC-WII or TC-W3 oils are recommended.
- Mobil Outboard Plus can also be used for light to moderate duty, air-cooled two-stroke engines used in power mowers, chain saws, leaf blowers and lawn trimmers.

Specifications and Approvals

Mobil Outboard Plus meets or exceeds the following industry requirements:

API TC

NMMA TC-W3



Typical Properties

Mobil Outboard Plus

Viscosity, ASTM D 445

cSt @ 40° C	52.9
cSt @ 100° C	8.8
Sulfated Ash, wt%, ASTM D 874	a
Pour Point, °C, ASTM D 97	-36
Flash Point, °C, ASTM D 92	114
Density @15° C kg/l, ASTM D 4052	a
Colour	Blue

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Outboard Plus are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.