

# Mobil Super 1000

## Premium Multigrade Passenger Vehicle Engine Oils

### Product Description

The Mobil Super 1000 products are a range of quality premium mineral motor oils designed to provide a high level of performance and protection under most operating conditions.

### Features and Benefits

Mobil Super 1000 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and extends engine life.

- Excellent wear protection
- Excellent engine cleanliness

### Applications

Mobil Super 1000 5W-30 is suitable for use in gasoline powered vehicles. Mobil Super 1000 10W-30, 10W-40, 15W-50 and 20W-50 are suitable for use in both gasoline and diesel powered vehicles. All Mobil Super 1000 products are ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions.

### Specifications and Approvals

Mobil Super 1000	5W-30	10W-30	10W-40	15W-50	20W-50
API SM	X	X	X	X	X
API SL	X	X	X	X	X
API CF		X	X	X	X

### Typical Properties

Mobil Super 1000	5W-30	10W-30	10W-40	15W-50	20W-50
SAE Grade	5W-30	10W-30	10W-40	15W-50	20W-50
Viscosity, ASTM D 445					
cSt @ 40°C	68.0	65.5	101	147	171
cSt @ 100°C	11.1	10.5	14.5	18.4	18.9
Viscosity Index, ASTM D 2270	155	149	148	140	125
Sulfated Ash, wt%, ASTM D 874	0.8	0.8	0.8	0.8	1.0
HTHS Viscosity., mPa•s @ 150°C, ASTM D4683	3.3	3.2	3.9	4.6	4.7
Pour Point, °C, ASTM D 97	-39	-36	-33	-30	-27
Flash Point, °C, ASTM D 92	230	220	220	234	240



**Mobil Super 1000**

Density @ 15 °C, kg/l, ASTM D4052	0.860	0.870	0.870	0.875	0.880
-----------------------------------	-------	-------	-------	-------	-------

**Health and Safety**

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

*The Mobil logotype, the Pegasus and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.*

**ExxonMobil Lubricants & Specialties**

All products may not be available locally. For more information, contact your local sales office or visit [www.exxonmobil.com](http://www.exxonmobil.com).

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.