

Mobil Super 4T 10W-40, 15W-40, 15W-50, 20W-50

High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super 4T 10W-40, 15W-40, 15W-50, 20W-50 are high performance conventional four-stroke motorcycle engine oils primarily intended for general use in all types of four-stroke motorcycles and engines.

Features and Benefits

Mobil Super 4T 10W-40, 15W-40, 15W-50, 20W-50 combine highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Extends engine life
Thermal and oxidation stability	Keeps engines clean for smoother operation
Good corrosion protection	Protects critical engine components
Broad viscosity range	Year round engine protection and performance

Applications

Mobil Super 4T 10W-40, 15W-40, 15W-50, 20W-50 are recommended for lubrication of all four-stroke motorcycle engines where an API SG and JASO MA level performance is recommended.

Specifications and Approvals

Mobil Super 4T meets or exceeds the following industry specifications:	10W-40	15W-40	15W-50	20W-50
API	SG	SG	SG	SG
JASO MA	MA	MA	MA	MA

Typical Properties

Mobil Super 4T	10W-40	15W-40	15W-50	20W-50
SAE Grade	10W-40	15W-50	20W-40	20W-50
Viscosity, ASTM D 445				
cSt @ 40° C	98	145	107	146.1
cSt @ 100° C	14.4	19.1	14.4	17.2
Viscosity Index, ASTM D 2270	156	152	141	128.2



Mobil Super 4T	10W-40	15W-40	15W-50	20W-50
Sulfated Ash, wt%, ASTM D 874	0.91	0.91	0.91	0.91
Pour Point, °C, ASTM D 97	-27	-24	-24	-24
Flash Point, °C, ASTM D 92	a	a	a	a
Density @15° C kg/l, ASTM D 4052	a	a	a	a

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Super 4T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.