

# Mobil Super S Plus 10W-40

## High Performance Multigrade Passenger Vehicle Engine Oil

### Product Description

Mobil Super S Plus 10W-40 is a high performance synthetic blend engine oil that exceeds the latest industry performance standards required in today's gasoline and diesel automobile engines.

### Features and Benefits

Mobil Super S Plus 10W-40 keeps engines cleaner and better protected than standard conventional mineral oils through a special combination of conventional and synthetic base oils and a carefully matched performance additive system. These synthetic blends enhance the oil's overall performance. Mobil Super S Plus 10W-40 actively maintains overall engine cleanliness preventing the build up of harmful deposits, sludge and varnish; fighting wear at low and high temperatures.

- Reduced build-up of harmful sludge and deposits produced in the hot zones within an engine
- Reduced wear which can lead to lower maintenance costs
- Longer engine life and reliable operation
- Improved lubrication at normal and high temperatures
- Enhanced high and low temperature protection in severe driving conditions

### Applications

Mobil Super S Plus 10W-40 is specifically recommended for use in high performance, turbocharged gasoline and diesel engines, as well as older normally aspirated models. Mobil Super S Plus 10W-40 is an excellent choice for passenger cars, light trucks and vans.

### Specifications and Approvals

---

**Mobil Super S Plus meets or exceeds the following 10W-40 industry specifications:**

---

ACEA	A3/B3
API	SM,SL,CF

---

**Mobil Super S Plus has the following builder approvals:** **10W-40**

---

MB-Approval	229.1
VW	505 00

---

**Mobil Super S Plus is recommended for use in applications requiring:** **10W-40**

---

VW	500 00
----	--------

---



## Typical Properties

### **Mobil Super S Plus 10W-40**

Viscosity, ASTM D 445

cSt @ 40° C	95.8
cSt @ 100° C	14.5
Sulfated Ash, wt%, ASTM D 874	1.0
Phosphorous	0.14
Flash Point, °C, ASTM D 92	231
Density @15° C kg/l, ASTM D 4052	0.87
Pour Point, °C, ASTM D 97	-30

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

*The Mobil logotype, the Pegasus design, and Super S are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.*

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit [www.exxonmobil.com](http://www.exxonmobil.com).

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.