

Mobil Super XHP Plus 15W-40

High Performance Multigrade Passenger Vehicle Engine Oils

Product Description

Mobil Super XHP Plus 15W-40 is a premium performance mineral motor oil designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Mobil Super XHP Plus 15W-40 is meticulously engineered for today's tougher engine specifications. It provides excellent engine protection against harmful deposits, sludge and varnish. Mobil Super XHP Plus 15W-40 helps keep engines clean and extend engine life.

- Improved wear protection
- Improved engine cleanliness
- Improved high and low temperature protection in severe driving conditions

Applications

Mobil Super XHP Plus 15W-40 is suitable for use in both gasoline and diesel powered vehicles. It can be used for highway or frequent stop-start driving conditions. Mobil Super XHP Plus 15W-40 is suitable for use in passenger cars, light trucks and vans.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super XHP Plus

Meets API SM/CF and ACEA A3/B3

Approved against MB-Approval 229.1 and VW 505.00

Typical Properties

Mobil Super XHP Plus

SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	109
cSt @ 100°C	14.5
Viscosity Index, ASTM D 2270	136
Sulfated Ash, wt%, ASTM D 874	1.0
HTHS Viscosity, mPa•s @ 150°C, ASTM D4683	4.0



Mobil Super XHP Plus

Pour Point, °C, ASTM D 97	-39
Flash Point, °C, ASTM D 92	236
Density @ 15 °C, kg/l, ASTM D4052	0.88

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus and Super XHP are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.