



INUGEL CLASSIC

Ready to use cooling liquid

Anti-corrosion and anti freeze, Protection -25°C/-13°F

Nitrite free / Amine free / Phosphate free

TYPE OF USE

MOTUL INUGEL CLASSIC is a ready to use cooling liquid, four seasons, based on monoethyleneglycol, using non organic additives.

Recommended for all cooling systems : passenger cars, heavy duty, construction and agriculture vehicles, gardening, ships, stationary engines ...

PERFORMANCES

STANDARDS	ASTM D3306 BRITISH STANDARD 6580 AFNOR NF R 15-601 SAE J1034
-----------	---

Contains a bitterness agent to prevent from drinking : coolants and antifreezes have a sweet taste but are harmful.

Protects the cooling system from freezing and metallic parts from corrosion.
Provides an excellent thermal exchange and then engine cooling efficiency.
Seals, durits and plastic parts friendly.

RECOMMENDATIONS

Ready to use, do not add any water

Drain intervals : Refer to the manufacturers' recommendation.

Do not mix with organic products (AOT).

This product should not be used to protect drinking water systems against freezing.

PROPERTIES

Nitrite free, amine free, phosphate free.

Color	Visual	Green
Density at 15°C/68°F	ASTM D4052	1.056
PH	ASTM D1287	8.1
Initial crystallization	ASTM D1177	-23°C/-9°F
Freezing Protection		-25°C/-13°F
Pour Point	ASTM D97	-27°C/-16.6°F
Boiling Temperature		106°C/223°F
Alkalinity Reserve	ASTM D1121	4.7 mg KOH/g