



SPECIFIC

0710 - 0700 5W-40

Renault engine oil, Gasoline naturally aspirated and turbocharged, and Renault Sport range (RS), and Diesel without DPF (Diesel Particulate Filter).
EURO IV and EURO V emission level.

100% Synthetic

TYPE OF USE

Specifically designed for Renault group (Renault, Dacia, Samsung) recent cars fitted with EURO IV or EURO V engines requiring an approved Renault RN0710 or RN0700 oil.

Motul Specific 0710 0700 can also be use in all vehicles requiring an oil with ACEA A3/B4 or API SL/CF standards prior to Renault RN0710 and RN0700 specifications. When in doubt, please refer to the vehicle owner's manual.

PERFORMANCES

| | | |
|-----------|-------------------------------|-----------|
| STANDARDS | ACEA A3/B4 | API SL/CF |
| APPROVALS | Renault RN0710, RN0700 | |

Renault has developped RN0710 and RN0700 standards for oils able to endure the most severe thermal constrains along with modern after treatment systems compatibility.

The 100% synthetic base stock provides a high thermal stability and insure an outstanding resistance at high temperatures. Prevent from varnish and sludge to maintain engine cleanliness. Lower the risk of ring sticking.

Maximum protection and performance of the lubricant preserved even in the most extreme conditions (Renault Sport engines, sporty driving,...).

Low volatility for a reduced oil consumption and exceptional oxydation resistance of the oil to ensure extended oil drain intervals set by the carmaker.

RECOMMENDATIONS

Drain interval: according to manufactuer's recommendations and to be tune to your own use.
Do not mix with non RN0710 or RN0700 approved oils.

PROPERTIES

| | | |
|---------------------------------|------------|-------------------------|
| Viscosity grade | SAE J 300 | 5W-40 |
| Density at 20°C (68°F) | ASTM D1298 | 0.849 |
| Viscosity at 100°C (212°F) | ASTM D445 | 15.2 mm ² /s |
| Viscosity at 40°C (104°F) | ASTM D445 | 89.2 mm ² /s |
| HTHS viscosity at 150°C (302°F) | ASTM D4741 | 4.12 mPa.s |
| Viscosity index | ASTM D2270 | 180 |
| Pour point | ASTM D97 | -30°C / -22°F |
| Flash point | ASTM D92 | 230°C / 446°F |
| Sulfated ash | ASTM D874 | 1.16 % weight |
| TBN | ASTM D2896 | 9.7 mg KOH/g |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE.

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 - Site Web : www.motul.fr

07/08