



# SPECIFIC 0720

## 5W-30

**Lubricant for Renault Diesel engines with DPF.  
EURO IV and EURO V emission level.**

**100% Synthetic**

### TYPE OF USE

Specifically designed for the latest generation of Diesel engines with diesel particulate filter (DPF) from Renault group (Renault, Dacia, Samsung) requiring an approved Renault RN0720 oil, and meeting EURO IV or EURO V emissions level.

### PERFORMANCES

STANDARDS                    ACEA C4 / A3 / B4  
APPROVALS                    Renault RN0720

Renault has developed RN0720 standard for oils able to endure the most severe thermal constraints along with modern after treatment systems compatibility.

The very low Sulfated Ash level, and reduced Sulphur and Phosphorous content (Low SAPS) technology protect and extend lifetime of after treatment systems.

The 100% synthetic base stock provides a high thermal stability and insure an exceptional resistance at high temperatures. Prevent from varnish and sludge to maintain engine cleanliness. Lower the risk of ring sticking.

Maximum protection and performance of the lubricant preserved even in the most severe conditions. Low volatility for a reduced oil consumption and outstanding oxidation resistance of the oil to ensure extended oil drain intervals set by the carmaker.

Fullfil the most stringent performance and durability requirements through the Long Life Renault (LLR) test validation.

### RECOMMENDATIONS

Drain interval: refer to manufacturer's recommendations and tune to your own use.  
Do not mix with non RN0720 approved oils.

### PROPERTIES

Viscosity grade	SAE J 300	<b>5W-30</b>
Density at 20°C (68°F)	ASTM D1298	0.850
Viscosity at 100°C (212°F)	ASTM D445	11.9 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)	ASTM D445	68.1 mm <sup>2</sup> /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.55 mPa.s
Viscosity index	ASTM D2270	172
Pour point	ASTM D97	-36°C / -32.8°F
Flash point	ASTM D92	224°C / 435.2°F
Sulfated ash	ASTM D874	0.49 % weight
TBN	ASTM D2896	6.0 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.      Made in FRANCE.

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 - Site Web : [www.motul.fr](http://www.motul.fr)

07/08