

PRISTA OIL	SAFETY DATA SHEET !!! Read SDS before handling and disposing the product MSDS № M 026/1540 SDS is prepared in accordance with Annex 2 of Regulation (EC) №1907/2006	Issued on: 2008-09-15 Revised edition Supersedes 2005-01-01
	Prista® Multigas HD 15W-40	Стр.1/4

1.PRODUCT AND COMPANY IDENTIFICATION			
<u>Product name</u>	Prista® Multigas HD 15W-40		
<u>Product application</u>	Multigrade engine oil for engines burning methane		
<u>Company Identification</u>	"Prista Oil "-EAD – 46 Treti Mart blvd. 7002 Rousse, Phone: + 359 82 82 46 97 + 359 82 82 46 97, e-mail:information@prista-oil.bg		
<u>Emergency phone number</u>			
2. HAZARDS IDENTIFICATION			
Product is classified as dangerous according to the classification rules in Directives 67/548/EEC or 1999/45/EC. Classification: Xi-Irritant with risk phrase R43.			
<u>Acute effects of exposure to man</u>			
<u>Inhalation</u>	Vapours or mist in unusually high concentrations, as from exposure in poorly ventilated areas, may cause irritation of the nose and throat, headache, nausea and drowsiness.		
<u>Skin contact</u>	Brief contact is not irritating. Prolonged and repeated contact with this product may cause allergic skin reaction in sensitive, exposed persons.		
<u>Eye contact</u>	May cause minimal irritation, experienced as temporary discomfort.		
<u>Ingestion</u>	No adverse effects expected. If more than several mouthfuls are swallowed, abdominal discomfort, nausea and diarrhea may occur.		
<u>Effect of exposure to the environment</u>	May form an oil film leading to de-oxygenation of water and possible harmful effect on aquatic life. Product can penetrate soil until reaching the surface of ground water (in the presence of ground water).		
3.COMPOSITION/INFORMATION ON INGREDIENTS			
<u>Name</u>	<u>% Wt</u>	<u>CAS No. / EINECS No.</u>	<u>R phrases and symbols</u>
Distillates (petroleum), solvent-dewaxed heavy paraffinic	< 78.0	64742-65-0/ 265-169-7	None
Calcium alkyl salicylate	<1.35	Unknown	R52/53
Zinc alkyldithiophosphate	< 1.35	272-028-3	Xi R36/38,NR51/53
Calcium sulfonate	< 1.35	Polymer	Xi R43
Alkylphenyl ether	< 0.15	Polymer	Xi R36/38, NR51/53
DMSO content (IP 346)	<3.0		
4. FIRST AID MEASURES			
<u>Inhalation</u>	If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.		
<u>Skin contact</u>	Wash skin with plenty of soap and water for several minutes. Get medical attention if skin irritation develops or persists		
<u>Eye contact</u>	Flush eyes with plenty of water for several minutes. Get medical attention if eye irritation persists.		
<u>Ingestion</u>	DO NOT INDUCE VOMITING. Get medical attention. Never give anything by mouth to an unconscious or convulsing person.		
<u>Instructions for physicians/doctors</u>	If nausea or irritations do not appear after ingestion, give medical carbon in water slurry (3 tablespoons in one liter water).		
5. FIRE-FIGHTING MEASURES			
<u>Suitable extinguishing media</u>	Use water fog, dry powder, foam or carbon dioxide. Use water to cool fire-exposed containers. If the leak or spill has not ignited, use water fog to disperse the vapours and to provide protection for personnel attempting to stop the leak.		
<u>Extinguishing media which must not be used for safety reasons</u>	Water jet		
<u>Special exposure hazards arising from the preparation</u>	None		

<u>Special protective equipment for the fire-fighters</u>	The nature of special protective equipment required will depend upon the size of the fire, the degree of confinement of the fire and the natural ventilation available. Fire-resistant clothing and self-contained breathing apparatus is recommended for fires in confined spaces and poorly ventilated areas. Full fireproof clothing is recommended for any large fires involving this product.
<u>Firefighting procedure</u>	In case of fire - Always call the fire brigade. Small fires, such as those capable of being fought with a hand-held extinguisher, can normally be fought by a person who has received instruction on the hazards of flammable liquid fires. Fires that are beyond that stage should only be tackled by people who have received hands-on training. Ensure escape path's available.
6. ACCIDENTAL RELEASE MEASURE	
<u>Personal precautions</u>	Personal Protective Equipment must be worn. Ventilate area if spilled in confined space or other poorly ventilated areas.
<u>Environmental precautions</u>	Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material.
<u>Cleaning materials</u>	Sand, sawdust
7. HANDLING AND STORAGE	
<u>Handling</u>	Avoid prolonged or repeated contact with skin. Avoid breathing of vapours
<u>Storage</u>	Keep containers closed when not in use. Store at ambient temperature
<u>Specific use</u>	In accordance with product specification
8. EXPOSURE CONTROL/PERSONAL PROTECTIN	
<u>Exposure Limits</u>	5 mg/m ³ of air for mineral oil mist averaged over an 8 hour daily exposure
<u>Exposure control</u>	Under normal use conditions, respirator is not usually required. If vapor or mist is generated, use approved respirator as appropriate. Certified air respiratory protection should be used for cleaning large spills or upon entry into tanks, vessels, or other confined spaces. Neoprene gloves; time for wearing out the gloves material >30 minutes. Safety goggles Exposed employees should exercise reasonable personal cleanliness. This includes cleansing exposed skin areas several times daily with soap and water and laundering or dry cleaning soiled work clothing. Long sleeve shirt is recommended. Use chemically protective boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction. May form an oil film leading to de-oxygenation of water and possible harmful effect on aquatic life. Product can penetrate soil until reaching the surface of ground water (in the presence of ground water).
<u>Respiratory protection</u>	
<u>Hand protection</u>	
<u>Eye protection</u>	
<u>Skin protection</u>	
<u>Environmental exposure controls</u>	
9. PHYSICAL AND CHEMICAL PROPERTIES	
9.1. General information	
Appearance	Brown liquid
Odour	Specific
9.2. Important health, safety and environmental information	

pH	Not applicable
Boiling point/Boiling range	-
Flammability/ Flashpoint, °C, COC	224
Explosive properties	-
Oxidising properties	-
Vapour pressure	-
Density at 20°C, g/ml	0.882
Solubility	Soluble in organic solvents
Water solubility	Insoluble
Partition coefficient: n-octanol/water	-
Kinematic viscosity ,cSt	13.8 cSt at 100°C
Vapour density	-
Evaporation rate	-
10. STABILITY AND REACTIVITY	
Conditions to avoid	Material is normally stable at moderately elevated temperatures and pressures
Materials to avoid	Oxidizing agent
Hazardous decomposition products	Smoke, carbon monoxide and other products of incomplete combustion
11. TOXICOLOGICAL INFORMATION	
Eye contact	Not expected to cause eye irritation. Base oil tested in accordance with Method OECD 405. May cause minimal irritation or redness if accidental eye contact occurs.
Skin contact	LD ₅₀ (rabbits) for base oil is > 2000mg/kg - Not expected to be skin irritant Base oil tested in accordance with OECD 404. Prolonged or repeated skin contact as from clothing wetted with material may cause dermatitis.
Inhalation	If material is misted or if vapours are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract.
Ingestion	LD ₅₀ (rats) for base oil is > 5000mg/kg- consider very low toxicity. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhea
Chronic	Repeated skin contact may cause a persistent irritation or dermatitis.
12. ECOLOGICAL INFORMATION	
Ecotoxicity	LC ₅₀ for base oil (96 hours for fish) is > 1000mg/l EC ₅₀ for base oils (48 hours for Daphnia is > 1000mg/l Very low toxicity
Mobility	Low, due to low water solubility. Spillage may penetrate the soil causing ground water contamination
Persistence and degradability	This product is not readily biodegradable. Information about base oil- Inherent biodegradability =22% after 28 days (OCD 301B)
Bioaccumulative potential	Log K _{OW} for base oils is in range 3.9-6.0. Partition coefficient n-octanol/water. A value Log K _{OW} > 3.0 indicates possible bioaccumulation.
Other adverse effects	May form an oil film leading to deoxygenation of water and possible harmful effect on aquatic life.
13. DISPOSAL CONSIDERATIONS	
Disposal of preparation and contaminated packaging	Always change used oils only at authorized places and shops! Dispose empty lubricant containers at approved for such wastes places. Follow all state or local regulations and requirements for disposal, recycle or reclaiming of waste oils and petroleum products.
Waste code	13 02 05 *(In accordance with European Waste Catalogue)
14. TRANSPORT INFORMATION	

	ADR - Not regulated IMDG - Not regulated RID - Not regulated IATA - Not regulated														
15. REGULATORY INFORMATION															
<u>Classification/ Labeling</u>	Under the criteria of Directives 67/548/EEC or 1999/45/EC special labeling is required: Xi- irritant with the following risk and safety phrases: R43- May cause sensitisation by skin contact S2- Keep out of reach of children S24- Avoid contact with skin S36/37- Wear suitable protective clothing and gloves S46- If swallowed seek medical advice immediately and show this container or label Contains: Calcium sulfonate														
16. OTHER INFORMATION															
<u>Revised edition</u>	Revised edition														
<u>Changes indication</u>	<table> <thead> <tr> <th>ITEM</th><th>DATE</th></tr> </thead> <tbody> <tr> <td>12. Ecological information</td><td>01-01-2005</td></tr> <tr> <td>13. Disposal consideration</td><td>01-01-2005</td></tr> <tr> <td>3. Hazard identification</td><td>15-12-2005</td></tr> <tr> <td>4. First aid measure</td><td>15-12-2005</td></tr> <tr> <td>5. Fire-fighting measure</td><td>15-12-2005</td></tr> <tr> <td>Revised edition according to Regulation (EC) 1907/2006</td><td>15-09-2008</td></tr> </tbody> </table>	ITEM	DATE	12. Ecological information	01-01-2005	13. Disposal consideration	01-01-2005	3. Hazard identification	15-12-2005	4. First aid measure	15-12-2005	5. Fire-fighting measure	15-12-2005	Revised edition according to Regulation (EC) 1907/2006	15-09-2008
ITEM	DATE														
12. Ecological information	01-01-2005														
13. Disposal consideration	01-01-2005														
3. Hazard identification	15-12-2005														
4. First aid measure	15-12-2005														
5. Fire-fighting measure	15-12-2005														
Revised edition according to Regulation (EC) 1907/2006	15-09-2008														
<u>Full text of R phrases</u>	R43- May cause sensitisation by skin contact R36/38- Irritating to eyes and skin R53- May cause long-term adverse effects in the aquatic environment R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment														
<u>Literary reference</u>	This Safety Data Sheet is prepared in accordance with Annex II of Regulation 1907/2006 (EC) 67/548/ EEC (dangerous substances) 1999/45/EEC (dangerous preparation): 2001/58/EEC EUCLID Data Sheet for base oil – European commission-European Chemical Bureau														
This information is the best of our current knowledge, and is believed to be correct as of the date hereof, and is intended to describe the product only in terms of health and safety and environmental requirements. Since the conditions of use are outside our control, any recommendations and suggestions are made without guarantee															